

TARIK



DOWNLIGHT
EMPOTRAR / TECHO
RECESSED DOWNLIGHT / CEILING

100-277 Vca
50/60 Hz



CRI
>90

CREE

50 000 hrs
Vida útil

IP
20

ORIENTABLE 30°

ALUMINIO

B ○

7
W

610
Lm


3 000 K
Cálido

7
W

671
Lm

4 000 K
Neutro

- | | | | |
|--------------------------------|------------------------------------|--------------------------------|------------------------------------|
| ☐ AT3573B | ☐ on
off | ☐ AT3574B | ☐ on
off |
| ☐ AT3573OB | ☐ 0-10
V | ☐ AT3574OB | ☐ 0-10
V |
| ☐ AT3573CB | ☐ TRIAC | ☐ AT3574CB | ☐ TRIAC |
| ☐ AT3573DB | ☐ DALI | ☐ AT3574DB | ☐ DALI |



12
W

980
Lm


3 000 K
Cálido

12
W

1078
Lm

4 000 K
Neutro

- | | | | |
|---------------------------------|------------------------------------|---------------------------------|------------------------------------|
| ☐ AT35123B | ☐ on
off | ☐ AT35124B | ☐ on
off |
| ☐ AT35123OB | ☐ 0-10
V | ☐ AT35124OB | ☐ 0-10
V |
| ☐ AT35123CB | ☐ TRIAC | ☐ AT35124CB | ☐ TRIAC |
| ☐ AT35123DB | ☐ DALI | ☐ AT35124DB | ☐ DALI |



REFLECTORES DISPONIBLES:
AVAILABLE REFLECTORS:

PARA / TO
AT3573 / 4 O/C/D B

AA153574
⚡ Reflector 15°

AA353574
⚡ Reflector 35°

PARA / TO
AT35123 / 4 O/C/D B

AA153512
⚡ Reflector 15°

AA353512
⚡ Reflector 35°

PARA / TO
AT35183 / 4 O/C/D B

AA153518
⚡ Reflector 15°

AA353518
⚡ Reflector 45°