



346040

2 wire audio system power supply with 6 DIN modular housing. Power supply 110 – 240 Vac 50 – 60 Hz. On the output it supplies 26 Vdc rated low voltage, and a maximum rated current of 600 mA. It is protected on the PRI side (with fuses) against short circuit and overload. It is a SELV double insulation safety device

Technical features

Brand	BTicino
Rated voltage	110-240Vac
Frequency	50-60Hz
Modules	6
Protection class	IP30
Plant type	Audio 2Wires, Audio 2 fili
Operating temperature	5 - 45°C
Series	Accessories

Commercial data

Minimum quantity	1
Sales unit	1
EAN code	8005543480700

Technical documentation

↓ Technical Data Sheet	↓ Instruction Sheet
↓ DWG drawing	

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Certifications

IMQ.jpg
Image file found or type unknown