


YFTW1212DL, Covered Twin Ferrule For 12 AWG

By Burndy Catalog # YFTW1212DL

Covered Twin Ferrule For 12 AWG.



Features

- · Made of electrolytic copper, tin plated
- Smooth funnel entry to make wire insertion easier
- Secure contacting even after multiple reconnecctions
- Long-term contact resistance
- No fraying of strands
- No breakage of wire strands when wire is bent, under stress, or in vibration environment
- UL listed per UL486F requirements
- RoHS Compliant

Application

For Use On Copper Conductor

General

Catalog Number YFTW1212DL
Connector Type End Termination

EU RoHS Indicator Yes
Insulation Y
Material Copper
Plated Y

Plating Type Tin - Electro Plated Sub Brand FERRULES
Type Bootlace Ferrule

UPC 621945623118

Dimensions

Dimension - D inch

Dimension - D1 inch

Dimension - D2 inch

Dimension - Length Overall

O.16 in

O.15 in

O.35 in

O.91 in

inch

Conductor Related

Conductor - Copper Solid Size 12 AWG Conductor - Copper Str Size 12 AWG Conductor Size 12 AWG

Certifications And Compliance

Buy American Compliant Contact Manufacturer

Certification - CSA Approved No
Certification - ETL No
Certification - UL Recognized No
Certification - cULus No

Certified Listed TAA Compliant (All status valid

till December 2024)

Standards - Industry Standards UL486

Met

Standards - RoHS Compliance CM

Status

UL Listed Yes

Logistics

Carton Quantity 1
Minimum Pack Quantity 100

Product Assets

Catalogs - BURNDY Master Catalog - Section B - Small Compression

ompression

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog Interactive Catalog - BURNDY Full-Line Digital Catalog

Sales Drawings - 50111876

Specifications - YFTW1212DL