




097.42

Puente de 2 terminales para zócalos 95.P3 y 95.P5

097.42

Valor nominal


10 A - 250 V



097.00

Soporte para etiquetas de identificación para zócalos 95.P3 y 95.P5

097.00



86.30

Módulo temporizador serie 86

(12...24)V AC/DC; Bifunción: AI, DI; (0.05 s...100 h)

86.30.0.024.0000

(110...125)V AC; Bifunción: AI, DI; (0.05 s...100 h)

86.30.8.120.0000

(230...240)V AC; Bifunción: AI, DI; (0.05 s...100 h)

86.30.8.240.0000

Homologaciones (según los tipos):     



99.02

Homologaciones
(según los tipos):

Los módulos DC con
polaridad no estándar
(+A2) están disponibles
bajo pedido.

Módulos de señalización y protección CEM tipo 99.02 para zócalos 95.P3 y 95.P5

Diodo (+A1, polaridad estándar)	(6...220)V DC	99.02.3.000.00
LED	(6...24)V DC/AC	99.02.0.024.59
LED	(28...60)V DC/AC	99.02.0.060.59
LED	(110...240)V DC/AC	99.02.0.230.59
LED + Diodo (+A1, polaridad estándar)	(6...24)V DC	99.02.9.024.99
LED + Diodo (+A1, polaridad estándar)	(28...60)V DC	99.02.9.060.99
LED + Diodo (+A1, polaridad estándar)	(110...220)V DC	99.02.9.220.99
LED + Varistor	(6...24)V DC/AC	99.02.0.024.98
LED + Varistor	(28...60)V DC/AC	99.02.0.060.98
LED + Varistor	(110...240)V DC/AC	99.02.0.230.98
RC	(6...24)V DC/AC	99.02.0.024.09
RC	(28...60)V DC/AC	99.02.0.060.09
RC	(110...240)V DC/AC	99.02.0.230.09
Antirremancia*	(110...240)V AC	99.02.8.230.07

* Potencia adicional de disipación 0.9 W