

Serie 1000 Económico



Código	Dimensión	Flujo de Aire
1004	4"	120 m ³ /hr (71 CFM)
1005	5"	195 m ³ /hr (115 CFM)
1006	6"	320 m ³ /hr (188 CFM)

Serie 1100 Cuadrado



Código	Dimensión	Flujo de Aire
1104	4"	120 m ³ /hr (71 CFM)
1105	5"	195 m ³ /hr (115 CFM)
1106	6"	320 m ³ /hr (188 CFM)

| Contra | Cable y Clavija | 1105 incluye reductor 5 pg a 4 pg |

Serie 1200 Ultra Delgado



Código	Dimensión	Flujo de Aire
1204-BL 1204-MA	4"	120 m ³ /hr (71 CFM)
1205-BL 1205-MA	5"	195 m ³ /hr (115 CFM)
1206-BL 1206-MA	6"	320 m ³ /hr (188 CFM)

| Contra | Cable y Clavija | Rejilla trasera | Ducto Extralargo | 1205 incluye reductor 5 pg a 4 pg |

Serie 1300 Europeo



Código	Dimensión	Flujo de Aire
1304-BL 1304-INOX	4"	100 m ³ /hr (59 CFM)
1305-BL 1305-INOX	5"	195 m ³ /hr (115 CFM)
1306-BL 1306-INOX	6"	320 m ³ /hr (188 CFM)

| LED de operación |

Serie 2300 Australiano



Código	Dimensión	Flujo de Aire
2304-BL	4"	90 m ³ /hr (53 CFM)
2304-INOX	4"	90 m ³ /hr (53 CFM)

| Contra | Temperatura de operación máx: 45° C |