



034219/17



034223/21



034254



034205

Emp.	Ref.	Nylbloc™		
		■ Regletas de 12 bornes con tornillos imperdibles. ■ Temperatura ambiente -25 a +55°C según la norma IEC 060664-1. ■ Polipropileno autoextinguible. ■ Comportamiento al hilo incandescente según IEC 060695-2-11; a 750°C, extinción <5 seg. y a 850°C < 30 seg. ■ Aislamiento clase II.		
	Azul	Sección		Corriente
		(mm²)	AWG	máxima [A]
10	034203	6	12	41
10	034205	10	10	57
10	034207	16	8	76
10	034209	25	6	101
	Negro			
10	034211	2,5	14	24
10	034213	6	12	41
10	034215	10	10	57
10	034217	16	8	76
10	034219	25	6	101
	Blanco			
10	034221	2,5	14	24
10	034223	6	12	41
10	034225	10	10	57
10	034227	16	8	76

	Suprem™	- Regletas de 12 bornes hembra-macho de conexión rápida. - Temperatura ambiente -5 a +40°C PVC -40°C a +80°C. - Según la norma IEC 60664-1. - Aislamiento clase II.		
		Sección (mm²)	AWG	Corriente máxima (A)
5	034253	6	12	15
5	034254	10	10	25

CERTIFICACIONES



■ Características y dimensiones (mm)

Ref.	L	P	A
342 03	107	18	14,4
342 05	135,1	20,8	17,4
342 07	156,1	24,2	22,5
342 09	214	33	27,5
342 11	94	15,6	12,3
342 13	107	18	14,4
342 15	135,1	20,8	17,4
342 17	156,8	24,2	22,5
342 19	214	33	27,5
342 21	94	15,6	12,3
342 23	107	18	14,4
342 25	135	20,8	17,4
342 27	156,8	24,2	22,5
342 53	106	36	14
342 54	135	42	17

Negrita (Bold): Empaque obligatorio para entrega de planta.