

P17 Tempra Pro IP 66/67 - LV 16, 32, 63 y125 A

Tabla de selección

Conforme a la norma IEC 60309-1 y IEC 60309-2 IP 44 acorde a IEC 60529 IK 09 acorde a IEC 62262 Material: poliamida 6 Autoextinguible: 850 ° C (partes activas) / 650 ° C (caja de plástico).			FUNCIONES			
			TOMA DE SOBREPONER	TOMA DE EMPOTRAR	TOMA AÉREA	CLAVIJA RECTAS
LV						
100 a 130 V~ 50/60 Hz	16 A	2P+T	555351	555381	555301	555321
200 a 250 V~ 50/60 Hz	16 A	2P+T	555354	555384	555304	555324
		3P+T	555355	555385	555305	555325
	32 A	2P+T	555454	555484	555414	555434
		3P+T	555455	555485	555415	555435
	63 A	2P+T	058740	058720	058710	058700
		3P+T	058741	058721	058711	058701
380 - 415 V~ 50/60 Hz	63 A	3P+T	058744	058724	058714	058704
	125 A	3P+T	059106	059116	059136	059126
440 a 460 V~ 50/60 Hz para contenedores en refrigerio	32 A	3P+T		555491	555421	555441
480 a 500 V~ 50/60 Hz	32 A	3P+T	555462	555492	555422	555442
	63 A	3P+T	055348	058727	058717	058707