


	IP 65/67	IK 09	UGR <10	 +15° - 90°		 0.2 m	SEA SIDE SUITABLE		3 MacAdam
--	-------------	----------	------------	----------------	--	-----------	----------------------	--	--------------

Z5



LED						
K	CRI	W LED	W Total	Real Lm	Optics	Código
RGBW		9.8	9.8	151	Flood 71°	14304
SW 2700-3200-4000	80	9.8	9.8	314	Flood 50°	14306
24VDC						


Incluido
Conectores estancos IP67

14304 14306	100-277V				
	IP		u. min	u. max	Código
		ON-OFF	1	7	18140
	IP67	DALI	1	11	18164
		1-10V	1	14	18167

	Consultar equipo comercial para solución de control CASAMBI
--	---

	IP 65/67	IK 09	UGR <10	 +15° - 90°		 0.2 m	SEA SIDE SUITABLE			3 MacAdam
--	-------------	----------	------------	----------------	--	-----------	----------------------	--	--	--------------

Z5



LED						
K	CRI	W LED	W Total	Real Lm	Optics	Código
RGBW		24	24	370	Flood 71°	14307
SW 2700-3200-4000	80	24	24	769	Flood 50°	14308
24VDC						

14307 14308	100-277V				
	IP		u. min	u. max	Código
		ON-OFF	1	4	18124
	IP67	DALI	1	5	18164
		1-10V	1	5	18167

No incluido	
Caja de empotrar	14309
Cable de 5m con conectores rápidos estancos (05-E095)	14310
Cable de 5m con conectores rápidos estancos RGBW (05-E096)	14312

	Consultar equipo comercial para solución de control CASAMBI
--	---