

Basic 4,8

 50000h
L80 B20


3 MacAdam




 120°

BASIC
SOLUTION

COMPATIBLE
WITH LINEAL



LED							
IP	K	CRI	W	Real lm	W/1m	Real lm/1m	
20	3000	80	24	2524	4,8	504,6	15591 
	4000	80	24	2621	4,8	524,2	15592 
 P.526 24VDC DIM							



LED							
IP	K	CRI	W	Real lm	W/1m	Real lm/1m	
65	3000	80	24	1125	4,8	225	11627-C
	4000	80	24	1125	4,8	225	15586 
  10m  P.526 24VDC DIM							

Basic 9,6

 50000h
L80 B20

3 MacAdam




 120°


BASIC
SOLUTION

COMPATIBLE
WITH LINEAL

RECOM
TAGLIO DI LUCE



LED							
IP	K	CRI	W	Real lm	W/1m	Real lm/1m	
20	3000	80	48	5113	9,6	1022,6	15593
	4000	80	48	5309	9,6	1061,8	15594
	RGB	80	48	2607	9,6	521,4	15595
 P.526 24VDC DIM							



LED							
IP	K	CRI	W	Real lm	W/1m	Real lm/1m	
65	3000	80	48	4110	9,6	822	15182
	4000	80	48	-	9,6	987,4	15596
  8m  P.526 24VDC DIM							