



PLAY MÓDULOS




7W



LED										
K	CRI	W LED	Real Lm	V	Hz		mA	Ángulo		Código
2700	90	6.4	529	100-240	50-60	-	-	30°		15138
2700	90	6.4	529max	9	-	DIM	700max	30°		15200
3000	90	6.4	663	100-240	50-60	-	-	30°		15133
3000	90	6.4	663max	9	-	DIM	700max	30°		15134
4000	90	6.4	651	100-240	50-60	-	-	30°		15747
4000	90	6.4	651max	9	-	DIM	700max	30°		15746
18135	ON-OFF		1x min 1 max 1							
18139	ON-OFF		1 x min 2 max 3							
11614	PUSH/1-10V		1 x min 1 max 5							
11616	PUSH/1-10V/DALI		1 x min 1 max 5							
D-PC700MA30	PHASE CUT		1 x min 3 max 4							

13W



LED										
K	CRI	W LED	Real Lm	V	Hz		mA	Ángulo		Código
2700	90	11.9	957	36	-	DIM	350max	30°		15202
2700	90	11.9	957	100-240	50-60	-	-	30°		15139
3000	90	11.9	1330	36	-	DIM	350max	30°		15197
3000	90	11.9	1330	100-240	50-60	-	-	30°		15135
4000	90	11.9	1387	36	-	DIM	350max	30°		15742
4000	90	11.9	1387	100-240	50-60	-	-	30°		15743
18144	ON-OFF		1 x min 1 max 1							
18166	ON-OFF		1 x min 2 max 3							
11614	PUSH/1-10V		1 x min 1 max 3							
11616	PUSH/1-10V/DALI		1 x min 1 max 3							
D-PC350MA13	PHASE CUT		1 x min 1 max 1							

No incluido		
Óptica 15°	15136	
Óptica 50°	16245	
Confort visual blanco	16248	
Confort visual negro	16127	
Panel de abeja x 5	16154	
Difusor elíptico x 5	16155	
Difusor cuadrado x 5	16246	
Difuminador de halo x 5	16247	



Consultar equipo comercial para solución de control CASAMBI