

Sia Standard 225

14 BLANCO 60 NEGRO WT SIN MARCO



BODY MAT AL DIF MAT PC IP54 50000h L80 B20 2 MacAdam 80° LED CREE



ROUND / XL / CON MARCO
Ø225 H149 Ⓢ Ø215



ROUND / XL / SIN MARCO
Ø190 H149 Ⓢ Ø190

MODELO	VOLTAJE	KELVIN / CRI / UGR	ÁNGULO	ALIMENTACIÓN	ACABADO
15465 <input type="checkbox"/>	37 W	3000K / CRI80 3502lm / UGR <10,9	80°		
15466 <input checked="" type="checkbox"/>					
15467 <input type="checkbox"/>	37 W	3000K / CRI90 3282lm / UGR <10,9	80°		
15468 <input checked="" type="checkbox"/>					
15469 <input type="checkbox"/>	37 W	4000K / CRI80 3502lm / UGR <10,9	80°		
15470 <input checked="" type="checkbox"/>					
				<input checked="" type="checkbox"/> 1x1 ON-OFF 18114 <input checked="" type="checkbox"/> 1-10V/DALI/DMX 11631 <input checked="" type="checkbox"/> P.526	
15471 <input type="checkbox"/>	44,5 W	3000K / CRI80 4165lm / UGR <10,9	80°		
15472 <input checked="" type="checkbox"/>					
15473 <input type="checkbox"/>	44,5 W	3000K / CRI90 4102lm / UGR <10,9	80°		
15474 <input checked="" type="checkbox"/>					
15475 <input type="checkbox"/>	44,5 W	4000K / CRI80 4165lm / UGR <10,9	80°		
15476 <input checked="" type="checkbox"/>					
				<input checked="" type="checkbox"/> 1x1 ON-OFF 18115 <input checked="" type="checkbox"/> 1-10V/DALI/DMX 11631 <input checked="" type="checkbox"/> P.526	
15477	37 W	3000K / CRI80 3502lm / UGR <10,9	80°		
15478	37 W	3000K / CRI90 3282lm / UGR <10,9	80°		
15479	37 W	4000K / CRI80 3502lm / UGR <10,9	80°		
				<input checked="" type="checkbox"/> 1x1 ON-OFF 18114 <input checked="" type="checkbox"/> 1-10V/DALI/DMX 11631 <input checked="" type="checkbox"/> P.526	
15480	44,5 W	3000K / CRI80 4165lm / UGR <10,9	80°		WT
15481	44,5 W	3000K / CRI90 4102lm / UGR <10,9	80°		WT
15482	44,5 W	4000K / CRI80 4165lm / UGR <10,9	80°		WT
				<input checked="" type="checkbox"/> 1x1 ON-OFF 18115 <input checked="" type="checkbox"/> 1-10V/DALI/DMX 11631 <input checked="" type="checkbox"/> P.526	