


Advanced CRI98 N

Índice de reproducción cromática superior a 98, para la obtención de colores vivos y vibrantes, ideal para espacios Retail.

IP20 100 50000h L80 B20 3 MacAdam 120° COMPATIBLE WITH LINEAL




LED							Maximum xm.	
IP	K	CRI	W	Real lm	W/1m	Real lm/1m	xxx + xxx	xxx
20	3000	98	74,5	7820	14,2	1564	5	15598 N

xxx + xxx 5m ~~xxx~~ P.526 24VDC DIM

Advanced THIN 4mm N

Ancho reducido para efectos sutiles e instalaciones minimalistas.

IP20 100 50000h L80 B20 3 MacAdam 120° COMPATIBLE WITH LINEAL




LED							Maximum xm.	
IP	K	CRI	W	Real lm	W/1m	Real lm/1m	xxx + xxx	xxx
20	3000	90	48	3205	9,6	641	5	15599 N

xxx + xxx 5m ~~xxx~~ P.526 24VDC DIM

Advanced High Density 240 LED/MT N

Alta densidad de leds 240 x mt, ideal para instalaciones lineales continuas con Taglio di luce.

IP20 100 50000h L80 B20 3 MacAdam 120° COMPATIBLE WITH LINEAL RECOM TAGLIO DI LUCE



LED							Maximum xm.	
IP	K	CRI	W	Real lm	W/1m	Real lm/1m	xxx + xxx	xxx
20	3000	90	72	4651	14,2	930,2	7	15600 N

xxx + xxx 7 m ~~xxx~~ P.526 24VDC DIM