

Sia Lens Batwing N

WR

BLANCO / BLANCO

WN

NEGRO / NEGRO

WH

NEGRO / BLANCO

WL

BLANCO / NEGRO

WP

TRIMLESS / BLANCO

WQ

TRIMLESS / NEGRO

BODY MAT

AL

DIF MAT

PC

IP54

50000h

L80

B20

2 MacAdam

LED

CREE

BATWING / CON MARCO

Ø115 H51 Ø100

BATWING / SIN MARCO

Ø96 H51 Ø96

MODELO	VOLTAJE	KELVIN / CRI / UGR	ALIMENTACIÓN	ACABADO
15610	17,7W	3000K / CRI80 1323lm / UGR <19	500Ma	WN
15611	17,7W	3000K / CRI80 1323lm / UGR <19	500Ma	WR
15612	17,7W	4000K / CRI80 1323lm / UGR <19	500Ma	WN
15613	17,7W	4000K / CRI80 1323lm / UGR <19	500Ma	WR
1 x 1 ON-OFF 18143 ✓ PUSH/1-10V 11614 ✓ PUSH/1-10V/DALI 11616 ✓ P526				
15614	17,7W	3000K / CRI80 1323lm / UGR <19	500Ma	WP
15615	17,7W	3000K / CRI80 1323lm / UGR <19	500Ma	WQ
15616	17,7W	4000K / CRI80 1323lm / UGR <19	500Ma	WP
15617	17,7W	4000K / CRI80 1323lm / UGR <19	500Ma	WQ

Efectos luz

Batwing

A= 3 mts. H= 3 mts. d= 2 mts.
U= 0.69

LED S C4 ESTEVEZ

Downlights — Technical —

97