

Sia adjustable 170 N

☐ 14 BLANCO

☒ 60 NEGRO

☐ WT SIN MARCO



BODY MAT AL

DIF MAT PC



IP23

50000h
L80 B20

2 MacAdam



30°



360°

LED CREE



ROUND / BIG /
CON MARCO

Ø180 H166 Ø170



ROUND / BIG /
SIN MARCO

Ø166 H166 Ø166

MODELO	VOLTAJE	KELVIN / CRI / UGR	ÁNGULO	ALIMENTACIÓN EQUIPO NO INCLUIDO	ACABADO
15622 ☐ 15623 ☒	33,4 W	3000K / CRI80 2401lm (18°) / UGR <10,9	18°	900Ma	 
15628 ☐ 15629 ☒	33,4 W	4000K / CRI80 2401lm (18°) / UGR <10,9	18°	900Ma	 
15618 ☐ 15619 ☒	33,4 W	3000K / CRI80 2401lm (18°) / UGR <10,9	30°	900Ma	 
15624 ☐ 15625 ☒	33,4 W	4000K / CRI80 2401lm (18°) / UGR <10,9	30°	900Ma	 
15620 ☐ 15621 ☒	33,4 W	3000K / CRI80 2401lm (18°) / UGR <10,9	38°	900Ma	 
15626 ☐ 15627 ☒	33,4 W	4000K / CRI80 2401lm (18°) / UGR <10,9	38°	900Ma	 
☒ 1 x 1 PUSH/1-10V 11614 ☒ PUSH/1-10V/DALI 11616 ☒ P.526					
15632	33,4 W	3000K / CRI80 2401lm (18°) / UGR <10,9	18°	900Ma	WT 
15635	33,4 W	4000K / CRI80 2401lm (18°) / UGR <10,9	18°	900Ma	WT 
15630	33,4 W	3000K / CRI80 2401lm (18°) / UGR <10,9	30°	900Ma	WT 
15633	33,4 W	4000K / CRI80 2401lm (18°) / UGR <10,9	30°	900Ma	WT 
15631	33,4 W	3000K / CRI80 2401lm (18°) / UGR <10,9	38°	900Ma	WT 
15634	33,4 W	4000K / CRI80 2401lm (18°) / UGR <10,9	38°	900Ma	WT 
☒ 1 x 1 PUSH/1-10V 11614 ☒ PUSH/1-10V/DALI 11616 ☒ P.526					

Accesorios no incluidos



15421 Difusor elíptico x 1



16162 Panel de abeja x 1



15422 Difusor cuadrado x 1