

1,5W



LED CREE						
K	CRI	W	Real lm	mA		
2700	80	1,5	141	500 max.	10°	16490
3000	80	1,5	141	500 max.	10°	16491
4000	80	1,5	141	500 max.	10°	16492

	☒ 1 x min 1 max 4	
ON-OFF	18134	X
	☒ 1 x min 1 max 6	
ON-OFF	18143	X
	P.526	

3W





LED CREE						
K	CRI	W	Real lm	mA		
2700	80	3,2	329	350 max.	30°	15123
3000	80	3,2	346	350 max.	30°	15124
4000	80	3,2	363	350 max.	30°	15502

	☒ 1 x 1	
ON-OFF	18127	✓
ON-OFF	18129	✓
	☒ 1 x max.2	
CORTE DE FASE	D-PC350MA9	✓
	☒ 1 x max 3	
ON-OFF	18128	✓
	☒ 1 x max 9	
PUSH/I-10V	11614	✓
PUSH/I-10V/DALI	11616	✓
	P.526	

Accesorios no incluidos

- **16119**  50°
Only (3W) x 5
- **16431** Confort visual
- **16412** Kit empotrado hormigón para Ø40-42
- **16411** Kit empotrado hormigón para Ø36

- **16486** Difusor elíptico x 5
- **16487** Panel de abeja x 5
- **16488** Difuminador de halo x 5
- **16489** Screen x 5