

Drivers

L x W x H mm	IP	CLASS	V in	Frecuencia	V out	Corriente de Salida		Corriente (mA)	W min	W max	Factor de potencia	Corte de fase - Dimmable	Push	1-10V	DALI	
						min	max									
37 x 26 x 23	20		100-240	50-60 Hz	3-11.5	-	-	350	1	4	0,6	-	-	-	-	18127
51 x 25 x 18	68	-	90-260	50-60 Hz	2-12	-	-	350	1	3.6	0,6	-	-	-	-	18129
Ø55 x 22	20		100-120	50-60 Hz	17-26	-	-	350	6	9	0,9	X	-	-	-	D-PC350MA9
122 x 38 x 28	20		100-240	50-60 Hz	3-47	-	-	350	2	12	0,55	-	-	-	-	18128
80 x 34 x 19.4	20		100-240	50-60 Hz	2-23	-	-	550	1	10	0,61	-	-	-	-	18134
79.4 x 38.6 x 19.10	20		90-264	50-60 Hz	3-11	-	-	700	2	7.5	0,5	-	-	-	-	18135
84 x 57 x 29.5	20		90-264	50-60 Hz	11-36	-	-	700	10	25	0,9	-	-	-	-	18139
146.5 x 43.5 x 30	20		100-277	50-60 Hz	10-45	350	1050	-	-	30	0,95	-	-	-	-	18137
Ø65 x 27	20		100-120	50-60 Hz	13-18.5	-	-	700	9	13	0,9	X	-	-	-	D-PC700MA13
Ø55 x 22	20		100-120	50-60 Hz	8-13	-	-	700	5.6	9	0,9	X	-	-	-	D-PC700MA9
128.9 x 75.4 x 32	20		100-240	50-60 Hz	20-40	-	1050	1000	20	40	0,9	-	-	-	-	18114
128.9 x 75.4 x 32	20		100-240	50-60 Hz	25-50	-	-	1200	20	60	0,9	-	-	-	-	18115
124 x 79 x 22	20		100-240	50-60 Hz	2-72	350	1050	-	-	35	0,95	-	X	X	-	11614
124 x 79 x 22	20		100-240	50-60 Hz	2-72	350	1050	-	-	35	0,95	-	X	X	X	11616
129 x 76 x 30	20		100-240	50-60 Hz	2-44	1050	1200	-	-	40	0,95	-	-	X	X	11631
169 x 39 x 45	65/67	-	100-240	50-60 Hz	-	-	-	700	-	10	0,9	-	-	-	-	14232
195 x 61 x 39	65/67	-	100-240	50-60 Hz	-	-	-	700	-	20	0,9	-	-	-	-	14233

Fuente de Alimentación

L x W x H mm	IP	CLASS	V in	Frecuencia		V out	Corriente de Salida	W min	W max	Factor de potencia	
129 x 98 x 40	20	-	85-264	47-63Hz	X	24	DC	-	40	0,95	18131
159 x 97 x 38	20	B	85-264	47-63Hz	X	24	DC	-	60	0,95	18125
179 x 71 x 43	67	A	100-120	47-63Hz	X	24	DC	-	60	0,5	18140
223 x 71 x 43	67	-	100-120	47-63Hz	X	24	DC	-	100	0,5	18124
199 x 99 x 50	20	-	100-120	47-63Hz	X	24	DC	-	100	0,5	18141
199 x 110 x 50	20	B	85-264	47-63Hz	X	24	DC	-	150	0,95	18132
223 x 71 x 43	67	A	85-264	47-63Hz	X	24	DC	-	150	0,95	18133
215 x 115 x 30	20	-	90-264	47-63Hz	X	24	DC	-	350	0,95	18138
252 x 90 x 43	67	-	90-277	50-60Hz	X	24	DC	-	320	0,95	18142

Fuente de Alimentacion para Low Voltage Tracks Din Rail

L x W x H mm	IP	CLASS	V in	Frecuencia	V out	Corriente de Salida	W min	W max	Factor de potencia	
32 x 125.2 x 102	20	-	100-264	50-60Hz	48	DC	-	75	0,93	16450
40 x 125.2 x 113.5	20	-	100-264	50-60Hz	48	DC	-	120	0,93	16451
63 x 125.2 x 113.5	20	-	100-264	50-60Hz	48	DC	-	240	0,93	16452

Transformador

  12V AC													
L x W x H mm	IP	V in	Frecuencia	V out	Corriente de Salida		W min	W max					
149 x 68 x 115	68/ 1 MT	127	50 - 60Hz	12	AC	MAGNÉTICO	-	100	11151				
15 x 20 x 50	65	127	50 - 60Hz	12	AC	ELECTRONICO	-	50	TE-HAL-50				
15 x 20 x 50	65	127	50 - 60Hz	12	AC	ELECTRONICO	-	6	19000-L				