

278-S00

30 Amp, 125/250 Volt, NEMA 14-30R, 3P, 4W, Flush Mtg Outlet /Receptacle, Straight Blade, Industrial Grade, Grounding, Side Wired, Steel Strap, Black

30 Amp, 125/250 Volt, NEMA 14-30R, 3P, 4W, Flush Mtg Receptacle, Straight Blade, Industrial Grade, Grounding, Side Wired, Steel Strap - Black

WARNING: Do not use with single-gang wallboxes, single-gang mud rings or single-gang box extenders.

Built of durable thermoplastic, Leviton Power Receptacles — come equipped with heavy-gauge, double-wire copper alloy contacts. To ensure correct and speedy wiring, terminals have ID markings. Flush mount receptacles fit Leviton's wide range of 2.15"- diameter wallplates and mounting hardware is included.

UPC Code : 078477695319

Country Of Origin : Mexico

NEMA :  14-30R

Technical Information

AC Horsepower Ratings

At Rated Voltage : 2 HP

Electrical Specifications

Amperage : 30 A

Current Limiting : Full Rated Current

Dielectric Voltage :
Withstands 2000V per UL498

Grounding : Grounding

Pole : 3

Temperature Rise : Max 30C
after 50 cycles OL at 150
percent rated current

Voltage : 125/250 VAC

Wire : 4

Environmental Specifications

Flammability : Rated V-2 per
UL 94

Operating Temperature : -40°
C to 60°C

Material Specifications

Body Material : Polypropylene

Color : Black

Face Material : Polypropylene

Line Contacts : Brass Double-
Wipe

Strap Material : Galvanized
Steel

Mechanical Specifications

Product ID : Ratings are
permanently marked on device

Terminal Accom. : #4 AWG

Terminal ID : X (Brass screw
or Black screw) = Hot, Y (Brass

Product Features

Amperage : 30 A

Color : Black

NEMA : 14-30R

Voltage : 125/250 VAC

screw or Black screw) = Hot;
White (Silver screw) = Neutral;
Green (Green screw) = Ground

Standards and Certifications

ANSI : C73

CSA : 22.2 No 42, C22.2 No.
14, C22.2 No.65

File : E13399


NEMA : WD-6

NOM : NOM - ANCE

UL : UL 498, UL 486E

Warranty : 10-Year Limited

Wiring Diagram



SPECIFICATION SUBMITTAL

JOB NAME: 	CATALOG NUMBERS:
JOB NUMBER: 	

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)

5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/international/contacts

