



UPC Code: 078477888261

Country Of Origin: Mexico

NEMA : (5-20

25349-IGN

20 Amp 1-Gang Floor Box Assembly, Industrial Grade, Isolated Ground, Self-Grounding

1-Gang Floor Box Receptacle Assembly, 20 Amp, 125 Volt, NEMA 5-20R, 2P, 3W, Floor Mtg Duplex Receptacle, Isolated Ground, Nickel, Straight Blade, Industrial Grade, Self Grounding, Back & Side Wired, Steel Strap - Orange

For low profile, in-floor receptacle installations, our Floor Box Receptacle Assemblies are the perfect fit. Available in both 15 & 20 Amp 1- and 2-gang configurations, these devices are suitable for wood frame construction with carpet, wood, tile, and vinyl finished flooring. Common applications include a variety of uses from home office workstations to high-end stages and entertainment venues.

Technical Information

AC Horsepower Ratings

At Rated Voltage: 1 HP

Electrical Specifications

Amperage: 20 A

Current Limiting: Full Rated

Current

Dielectric Voltage:

Withstands 2000V per UL498

Grounding: Self-Grounding

Pole: 2

Temperature Rise: Max 30C after 50 cycles OL at 150 percent rated current

Voltage: 125 VAC

Wire: 3

Environmental Specifications

Flammability: Rated V-2 per

UL 94

Operating Temperature : -40°

C to 60°C

Material Specifications

Body Material: Nylon

Clamp Nuts : Zinc-Plated Steel

Color: Orange

Face Material: Nylon

Floorplate Material: Solid Nickel 0.060 In Thick

Ground Clips: Brass-Plated

Grounding Screw: Brass 8-32

Line Contacts: Brass Triple-

Wipe .031 Thick

Shutter Mechanism : Delrin®

Acetal

Strap Material: Zinc-Plated

Steel

Terminal Screws: Brass 8-32

Mechanical Specifications

Product ID: Ratings are permanently marked on device

Terminal Accom.: 14-10 AWG

Terminal ID: Brass-Hot, Green-Ground, Silver-Neutral

Termination: Back & Side

Product Features

Amperage: 20 A

Color: Orange

Function: Isolated Ground

NEMA: 5-20R

Type: Wood Frame

Voltage: 125 VAC

Standards and Certifications

ANSI: C-73

CSA C22.2 No. 42 : File

E152105

NEMA: WD-6


NOM: 057

UL498: File E13399


Warranty: 2-Year Limited

Wiring Diagram

Dimensional Drawing







SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S. T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52) 5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.