



Color :  Ivory

UPC Code : 078477208205

Country Of Origin : Mexico

NEMA :  10-20R

Available Colors :



Black



Ivory

5032-I

20 Amp Single Receptacle/Outlet, Commercial Grade, Dual Voltage

Single Receptacle Outlet, Commercial Specification Grade, Dual Voltage, Smooth Face, 20 Amp, 125/250 Volt, Side Wire, NEMA 10-20R, 3-Pole, 3-Wire, Non-Grounding - Ivory

Leviton's line of Heavy-Duty Specification Grade receptacles are designed and manufactured to withstand the most demanding environments. Available in a wide variety of configurations, including isolated ground, tamper-resistant, etc., these Commercial Grade devices are the electrical contractor's choice for use in hotels, schools, hospitals and commercial office buildings.

Technical Information

AC Horsepower Ratings

At Rated Voltage : 2 HP L-L /
1 HP L-N

Electrical Specifications

Amperage : 20 A

Current Limiting : Full Rated Current

Dielectric Voltage :
Withstands 2000V per UL498

Grounding : Non-Grounding

Pole : 3

Temperature Rise : Max 30C
after 50 cycles OL at 150
percent rated current

Voltage : 125/250 VAC

Wire : 3

Environmental Specifications

Flammability : Rated V-2 per
UL 94

Operating Temperature : -40°
C to 60°C

Material Specifications

Body Material : Nylon

Color : Ivory

Face Material : Nylon

Grounding Screw : Brass 8-32

Line Contacts : Brass Double
Wipe .031 Thick

Strap Material : Steel

Terminal Screws : Brass 8-32

Mechanical Specifications

Product ID : Ratings are
permanently marked on device

Screw Terminal Torque : 14-
18 in-lbs

Terminal Accom. : 14-10 AWG

Product Features

Color : Ivory

Device Type : Single
Receptacle Outlet

Feature 3 : Dual Voltage

Terminal ID : Brass-Hot (2x),
Silver-Neutral

Termination : Side Wire

Feature 4 : Smooth Face

Grade : Commercial
Specification Grade

NEMA : 10-20R

Standards and Certifications

ANSI : C-73

CSA C22.2 No. 42 : File
152105

NEMA : WD-6


NOM : 057

UL Fed Spec WC-596 : File
E13399

UL498 : File E13399

Warranty : 10-Year Limited

Wiring Diagram



SPECIFICATION SUBMITTAL

JOB NAME: 	CATALOG NUMBERS:
JOB NUMBER: 	

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)

5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.