



# 5362-IGG

20 Amp Isolated Ground Duplex Receptacle/Outlet, Industrial Grade, Self-Grounding, Isolated Ground

Isolated Ground Duplex Receptacle Outlet, Heavy-Duty Industrial Specification Grade, Smooth Face, 20 Amp, 125 Volt, Back or Side Wire, NEMA 5-20R, 2-Pole, 3-Wire, Self-Grounding - Gray

**ROHS Compliant** : Yes

Leviton's line of Extra Heavy-Duty Industrial Grade receptacles are designed and manufactured to withstand the harsh conditions typically associated with industrial environments. Available in a wide variety of configurations, including isolated ground, tamper-resistant, hospital grade, etc., these Industrial Grade devices are the electrical contractor's choice for use in factories, schools, hospitals and commercial office buildings.

**Color** :  Gray

**UPC Code** : 078477053287

**Country Of Origin** : Mexico

**NEMA** :  5-20R

## Available Colors :



## Technical Information

AC Horsepower Ratings

**At Rated Voltage** : 1 HP

Electrical Specifications

**Amperage** : 20 A

**Current Limiting** : Full Rated Current

**Dielectric Voltage** :  
Withstands 2000V per UL498

**Grounding** : Self-Grounding

**Pole** : 2

**Temperature Rise** : Max 30C  
after 250 cycles OL at 200  
percent rated current

**Voltage** : 125 VAC

**Wire** : 3

Environmental Specifications

**Flammability** : Rated V-2 per  
UL 94

**Operating Temperature** : -40°  
C to 60°C

Material Specifications

**Body Material** : Thermoplastic  
Nylon

**Clamp Nuts** : Galvanized Steel

**Color** : Gray

**Face Material** : Thermoplastic  
Nylon

**Grounding Screw** : Brass 8-32

**Isolated Ground System** :  
Brass

**Line Contacts** : Phosphor  
Bronze

**Strap Material** : Galvanized  
Steel

**Terminal Screws :** Plated  
Brass

Mechanical Specifications

**Product ID :** Ratings are  
permanently marked on device

**Screw Terminal Torque :** 14-  
18 in-lbs

**Terminal Accom. :** 14-10 AWG

**Terminal ID :** Brass-Hot,  
Green-Ground, Silver-Neutral

**Termination :** Back or Side  
Wire

**Torque Range :** 14-16 inch  
pounds

Product Features

**Body Material :** Thermoplastic  
Nylon

**Color :** Gray

**Device Type :** Duplex  
Receptacle Outlet

**Face Material :** Thermoplastic  
Nylon

**Feature 4 :** Smooth Face

**Grade :** Heavy-Duty Industrial  
Specification Grade

**NEMA :** 5-20R

**Termination :** Back or Side  
Wire

Standards and Certifications

**ANSI :** C-73

**CSA C22.2 No. 42 :** File  
152105

**NEMA :** WD-6

**NOM :** 057

**UL Fed Spec WC-596 :** File  
E13399

**UL498 :** File E13399

**Warranty :** 10-Year Limited

**SPECIFICATION SUBMITTAL**

<b>JOB NAME:</b> <input type="text"/>	<b>CATALOG NUMBERS:</b> <input type="text"/>	
<b>JOB NUMBER:</b> <input type="text"/>	<input type="text"/>	<input type="text"/>

**Leviton Manufacturing Co., Inc**

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.  
T. Monday-Friday): +1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·  
FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)  
5386- 1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

Visit our Website at: [www.leviton.com](http://www.leviton.com)

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to:  
[www.leviton.com/international/contacts](http://www.leviton.com/international/contacts)

**© 2024 Leviton Manufacturing Co., Inc.**