



5362-SGW

20 Amp Duplex Receptacle/Outlet, Industrial Grade, Tamper-Resistant, Self-Grounding

Duplex Receptacle Outlet, Extra Heavy-Duty Industrial Specification Grade, Tamper-Resistant, Smooth Face, 20 Amp, 125 Volt, Back or Side Wire, NEMA 5-20R, 2-Pole, 3-Wire, Self-Grounding - White

ROHS Compliant : Yes

Technical Information

AC Horsepower Ratings

At Rated Voltage : 1 HP

Electrical Specifications

Amperage : 20 A

Dielectric Voltage :
Withstands 2000V per UL498

Grounding : Self-Grounding

Pole : 2

Temperature Rise : Max 30C
after 250 cycles OL at 200
percent rated current

Voltage : 125 VAC

Wire : 3

Environmental Specifications

Flammability : Rated V-2 per
UL 94

Operating Temperature : -40°
C to 75°C

Material Specifications

Body Material : Nylon

Face Material : Nylon

Ground Clips : Brass

Grounding Screw : Brass 8-32

Line Contacts : Triple-Wipe .
040" High Performance Brass
Alloy

Strap Material : Brass .050"

Terminal Clamp : Zinc-Plated
Steel

Terminal Screws : Brass 10-32

Mechanical Specifications

Product ID : Ratings are
permanently marked on device

Screw Terminal Torque : 14-
18 in-lbs

Terminal Accom. : 14-10 AWG

Terminal ID : Brass-Hot,
Green-Ground, Silver-Neutral

Product Features

Color : White

Device Type : Duplex
Receptacle Outlet

Feature : Tamper-
Resistant|Smooth Face

Grade : Extra Heavy-Duty
Industrial Specification Grade

NEMA : 5-20R

Color :  White

UPC Code : 078477868720

Country Of Origin : Mexico

NEMA :  5-20R

Available Colors :


Brown

Gray


Blue

Ivory


Black

Red

Termination : Back or Side
Wire

Wire Type : Solid or Stranded
Building Wire

Standards and Certifications

ANSI : C-73

Applicable Standards : UL
498, CSA C22.2 No. 42,
FedSpec W-C 596

Certification/Listing : UL,
CSA, NOM-ANCE

NEMA : WD-1 & WD-6

Warranty

Warranty : 10-Year Limited

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·
FAX: +1-800-824-3005 ·

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 ·

Visit our Website at: www.leviton.com

© 2025 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without
notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/company/about-leviton/locations

© 2025 Leviton Manufacturing Co., Inc.