



5374-S00

50 Amp, 250 Volt, 2P, 3W, Flush Mtg Receptacle, Straight Blade, Industrial Grade, Grounding, Black

50 Amp, 250 Volt, NEMA 6-50R, 2P, 3W, Flush Mtg Receptacle, Straight Blade, Industrial Grade, Grounding, Side Wired, Steel Strap - Black **WARNING:** Do not use with single-gang wallboxes, single-gang mud rings or single-gang box extenders.

Built of durable thermoplastic, Leviton Power Receptacles — come equipped with heavy-gauge, double-wire copper alloy contacts. Flush mount receptacles fit Leviton's wide range of 2.15" -diameter wallplates and mounting hardware is included.

UPC Code : 078477695401

Country Of Origin : Mexico

NEMA :  6-50R

Technical Information

AC Horsepower Ratings

At Rated Voltage : 3 HP

Electrical Specifications

Amperage : 50 A

Current Limiting : Full Rated Current

Dielectric Voltage :
Withstands 2000V per UL498

Grounding : Grounding

Pole : 2

Temperature Rise : Max 30C
after 50 cycles OL at 150
percent rated current

Voltage : 250 VAC

Wire : 3

Environmental Specifications

Flammability : Rated V-2 per
UL 94

Operating Temperature : -40°
C to 60°C

Material Specifications

Body Material : Polypropylene

Color : Black

Face Material : Polypropylene

Line Contacts : Brass Double-
Wipe

Strap Material : Galvanized
Steel

Mechanical Specifications

Product ID : Ratings are
permanently marked on device

Terminal Accom. : #4 AWG

Terminal ID : Brass screws =
Hot; Green screw = Ground

Product Features

Color : Black

NEMA : 6-50R

Standards and Certifications

ANSI : C73

CSA : 22.2 No 42, C22.2 No.
14, C22.2 No.65

File : E13399


NEMA : WD-6

NOM : NOM - ANCE

UL : UL 498, UL 486E

Warranty : 10-Year Limited

Wiring Diagram



SPECIFICATION SUBMITTAL

JOB NAME: JOB NUMBER:	CATALOG NUMBERS: <table border="1" style="width: 100%; border-collapse: collapse;"><tr><td style="width: 50%; height: 20px;"></td><td style="width: 50%; height: 20px;"></td></tr><tr><td style="height: 20px;"></td><td style="height: 20px;"></td></tr></table>				

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·
FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without
notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.