



**Color:** Black

**UPC Code:** 07847732628

**Country Of Origin:** Mexico

**NEMA:**  
Non-NEMA



## CS6369

50Amp, 125/250V AC, Non-NEMA, 3P, 4W, Black & White Locking Flush Mount Receptacle, Industrial Grade, Grounding, California-Style(CS) – BLACK

Leviton's Black & White 50 Amp, Non-NEMA line of industrial grade locking blade devices feature rugged construction that resists impact, sunlight, chemicals and rough use. All contacts and blades are solid one-piece construction for superior conductivity. Corrosion resistant versions feature nickel plated contacts and blades, plus stainless steel shrouds and screws. The ergonomic, fluted-body design with radial gripping edge is ideal for gripping and pulling. The unique cord clamp accepts a wide range of cord sizes, providing a secure grip without damaging the cord. And, they are backed by a limited lifetime warranty.

### Technical Information

#### Electrical Specifications

**Amperage:** 50 A

**Current Interrupting:** Certified for current interrupting at full rated current

**Dielectric Voltage Withstand:** 2000V minimum per UL 498

**Grounding:** Grounding

**Maximum Working Voltage:** 125/250V as rated

**Pole:** 3

**Temperature Rise:** Max 30°C temp rise at full-rated current after 150 cycles of OL at 150% rated DC current

**Voltage:** 125/250 VAC

**Wire:** 4

#### Environmental Specifications

**Environment:** Dry

**Flammability:** Rated HB or better UL94

**Operating Temperature:** -40°C to 75°C

#### Material Specifications

**Assembly Rivets:** SS 302/304

**Back Cover:** Reinforced Nylon

**Body & Contract Carrier:** Reinforced Nylon

**Body Material:** Impact Modified Nylon

**Box Terminal:** 0.062inch thick Copper

**Center Pin:** SS 302/304

**Color:** Black

**Connector Contact - Binding Plate:** 0.100inch thick Brass

**Connector Contact - Spring:** 0.041inch thick Brass

**Contact Rivet:** Brass

**Face Module:** Reinforced Nylon

**Mounting Screws:** SS 302/304

**Mounting Strap:** Single piece SS 302/304

**Shroud:** .062inch thick Nickel Plated Steel

**Terminal Set Screw:** SS 302/304

#### Mechanical Specifications

**Product ID:** Ratings and Catalogue No. molded into face

**Terminal Accom.:** #10min to #6max AWG Solid or Stranded Wire (Stranded Wire for Ground only)

**Terminal ID:** X, W, Y, Z and Green for ground

#### Product Features

**Brand:** Black and White

**Color:** Black

**Device Type:** Locking Receptacle

**NEMA:** Non-NEMA

#### Standards and Certifications


**CSA C22.2 No. 42:** File 152105

**NOM:** 057

**RoHS:** Compliant

**UL 498:** File E13399

**Warranty:** Lifetime Limited



## SPECIFICATION SUBMITTAL

<b>JOB NAME:</b> <input type="text"/> <b>JOB NUMBER:</b> <input type="text"/>	<b>CATALOG NUMBERS:</b> <input type="text"/> <input type="text"/> <input type="text"/> <input type="text"/>
---	---

### Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):  
+1-800-824-3005

### Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·  
FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

### Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-  
1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

Visit our Website at: [www.leviton.com](http://www.leviton.com)

© 2018 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

### Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:  
[www.leviton.com/international/contacts/](http://www.leviton.com/international/contacts/)

