

32277-DY3

Type 2 3-Phase Surge Panel

277/480V, 220/380V, 480V 3-Phase WYE or Delta, Surge Panel, Decora Home Control & X10 Compatible, NEMA 3R Enclosure, UL 1449 4th Edition Type 2

DISCONTINUED

Suggested Replacement SKUs: :

Leviton's Surge Protection Devices can be used individually or as part of a coordinated application strategy, to protect sensitive electronic equipment, in industrial, commercial and residential locations, from the stress and degradation inflicted by voltage transients. Leviton Surge Protection Devices are compliant with UL 1449 Standards. Leviton's outstanding Surge Protection Devices divert damaging voltage transients, or surges, away from electronic equipment. Transients are diverted away from sensitive micro circuitry, providing protection against catastrophic failure, costly downtime and data disruptions.



UPC Code : 078477846599

Country Of Origin : Mexico

Technical Information

Electrical Specifications

EMI/RFI Noise Rejection : (-20 to -40 @ 1.5K - 1.2MHz)

Frequency : 50/60Hz

Recommended Circuit Breaker Rating : 30A, 277/480V

Surge Technology : 40mm MOV Design

Voltage Configuration : 220/380 V or 277/480 V, 3-Phase WYE; 240 V or 480 V, 3-Phase Delta

Environmental Specifications

Enclosure : Type 3R

Flammability : Rated V-2 per UL 94

Operating Temperature : -10° C to 60°C

Relative Humidity : 5% to 95% non-condensing

Storage Temperature Range : -20C to 85C

Material Specifications

Outer Enclosure : Powder Coated Steel

Mechanical Specifications

Connection Type : Parallel - Hardwired via 12 AWG Wire

Diagnostics : LED

Remote Monitoring : Dry Contact Leads-N.O./N.C. Form C Rated at 7Amps @ 240VAC or 30 VDC

Surge Counter : No

Performance Data

MCOV L-G : 640

MCOV L-L : 552

Product Features

Diagnostics : LED

MCOV : 320V AC

MCOV L-N : 320

Replaceable Modules : No

MCOV N-G : 320

**UL1449 Impluse 6kV/500A L-N
/N-G/L-L : 900/800/1500**

**Maximum Surge Current, Per
Mode (Per Phase) : 80kA
(160kA)**

**Nominal Discharge Current
Rating : 3kA**

**Short Circuit Current Rating :
100kA**

VPR L-G : 2000

VPR L-L : 1800

VPR L-N : 1200

VPR N-G : 1200

Standards and Certifications

Warranty

**ANSI/IEEE Category A, B and
C : C-62.41 & 62.45**

Warranty : 5-Year Limited

**UL 1449 4th Edition : cULus
Listed Type 2**

SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/>
JOB NUMBER: <input type="text"/>	<input type="text"/>

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)

5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.