


330P4WLEV



UPC Code : 078477921678

Country Of Origin : Mexico

LEV Series IEC Pin & Sleeve Plug

30 Amp, 125 Volt, 2P, 3W, LEV Series North American-Rated IEC 60309-1 & 60309-2 Pin & Sleeve Plug, Industrial Grade, IP66 /IP67/IP68/IP69K, Watertight - Yellow

LEV Series IEC 60309 Pin & Sleeve Devices are designed to simplify your installation, endure the harshest environments and improve safety and productivity:

- Threaded housing design removes several screws making installation quicker and easier
- Superior watertight ratings including IP69K for washdown /outdoor applications and industry exclusive IP68 for long-term submersion
- NSF certified sanitary design trusted for use in food & beverage facilities

Leviton Pin & Sleeve devices are UL listed components and suitable for use in prefabricated wiring assemblies when wired in accordance with UL 1007.

**Calculate
Time &
Money
Saved with
the LEV
Series
Calculator!**

Technical Information

Electrical Specifications

Amperage : 30 A

Current Interrupting : Certified for current interrupting at full-rated current and voltage

Dielectric Voltage : 3000V for 1 min.

Endurance : 1000 cycles rated V and I load, 1000 cycles no-load (30A)

Max. Voltage : 600V

Overload UL20 Test : 50 cycles

Pole : 2

SCCR : 200kA

Screw Terminal Torque : 20 in-lb

Environmental Specifications

Corrosion Resistance : Salt fog tested

Flammability : Rated V-0 (Contact Carrier), HB or better (Housing) per UL94

IP Rating : IP66, IP67, IP68, IP69K

NEMA Enclosure Type : 3R, 4X, 6P and 12

NSF : 14159-1, Hygenic Requirement for the Design of Meat & Poultry Processing Equipment

Operating Temperature : -40° C to 60°C (with impact)

UV Resistance : UV stabilized F1 rated housings

Temperature Rise : Max 30°C
rise at full rated current (after
overload)

Voltage : 125 VAC

Wire : 3

Material Specifications

Assembly Screws : 303
Stainless Steel

Contact Carrier : Glass filled
Nylon

Grommet/Gasket : NBR/Buna
N

Housing : Impact Modified
Nylon

Locking Ring : Impact
Modified Nylon

Terminal Screws : 303
Stainless Steel

Mechanical Specifications

Conductor Range : #12 AWG
to #8 AWG

Crush Test : 250 lbs for 1 min
after -25°C for 6 hrs

Hardware Head Type : Hex
style socket screws for
terminals, combination screws
for all others

Impact : Drop from 30" 8 times
after conditioning to -25°C, for 6
hoursDrop from 72" after
conditioning to -35°C, for 6
hours

Product Features

Clock Position : 4 o'clock

Color : Yellow

Configuration : North American

Device Type : Plug

Lockout/Tagout Provision :
Lockout hole on housing

Product Markings : Brand, UL,
CE and environmental ratings
molded in. Item number,
ampacity, voltage, phases, HP,
NSF on label

Series : LEV Series

Standards and Certifications

CE : CE certification

CSA : CSA C22.2 No 182.1-13
(Harmonized with UL 1682)

IEC Rating : 60309-1, 60309-2

NOM : NOM –ANCE standards

RoHS : RoHS compliant
components

UL : UL 1686 C2, UL 1682

Warranty

Warranty : 5-Year Limited

Patents*

US10431922

US11271342

This list is provided for patent marking purposes only. A good
faith effort is made to maintain the accuracy and completeness of
this list. No legal inference should be drawn from the omission of
a patent from this list.

SPECIFICATION SUBMITTAL

JOB NAME:

JOB NUMBER:

CATALOG NUMBERS:

--	--	--

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·
FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without
notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.