



UPC Code : 078477839027

Country Of Origin : Please Contact Customer Service

460R9W

60 Amp, 250 Volt 3-Phase, 3P, 4W, Outlet North American Pin & Sleeve Receptacle, Industrial Grade, IP67, Watertight - BLUE

DISCONTINUED

Suggested Replacement SKUs: :

Technical Information

Electrical Specifications

Amperage : 60 A

Current Interrupting : Certified for current interrupting at full rated current

Dielectric Voltage : 2000V for 1 min.

Endurance : Up to 1000 connects and disconnects, under load, at full rated current and voltage

Insulation Resistance : 500V for 1 min; $\geq 5M\Omega$

Phase : 3-Phase

Pole : 3

Temperature Rise : Max 30C after 50 cycles OL at 150 percent rated current

Voltage : 250 VAC

Wire : 4

Environmental Specifications

Corrosion Resistance :

Ferrous parts immersed in 20°C, 10 percent ammonium chloride solution for 10 min

Flammability : Rated V-0 per UL 94

IP Rating : IP67/IP69K

Moisture Resistance : Per UL 1682, immersed for 24 hours in 5cm of 25°C water

Material Specifications

Arm Spring : Performance Grade Stainless Steel

Body Material : Valox 357

Cover Eyelet : Nickel-Plated Brass

Cover with Arm : Valox 357

Gasket Material : Chloroprene

Mounting Flange : Valox 357

Phase and Ground Sleeves : Brass

Sleeve Spring : Stainless Steel

Terminal Screws : Steel

Mechanical Specifications

Crush Test : 250lbs for 1 min after -25°C for 6 hrs

Impact Resistance : Drop from 30" 8 times after conditioning to -25°C for 6 hrs

Minimum Withdrawal Force : 15lbs

Product Features

Color : Blue

Standards and Certifications

Configuration : North American **CE Marking :** Per low voltage directives 73/23/EEC, 93/68 /EEC

Device Type : Receptacle

CSA Certified : C22.2 No 182.1

IEC Rating : 60309-1 and 60309-2

UL Listed : 1682 and 1686

Warranty : 2-Year Limited

SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/>	
JOB NUMBER: <input type="text"/>	<input type="text"/>	<input type="text"/>

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)

5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.