



Color :  White

UPC Code : 078477443293

Country Of Origin : Mexico

NEMA :  5-15R

Available Colors :


Gray


Ivory

5040-CW

15 Amp Duplex Receptacle/Outlet, Commercial Grade, Self-Grounding

Duplex Receptacle Outlet, Commercial Specification Grade, Smooth Face, 15 Amp, 125 Volt, Pre-Wired Leads (hot and neutral), NEMA 5-15R, 2-Pole, 3-Wire, Self-Grounding - White

Leviton's line of Heavy-Duty Specification Grade receptacles are designed and manufactured to withstand the most demanding environments. Available in a wide variety of configurations, including isolated ground, tamper-resistant, etc., these Commercial Grade devices are the electrical contractor's choice for use in hotels, schools, hospitals and commercial office buildings

Technical Information

AC Horsepower Ratings

At Rated Voltage : 1/2 HP

Electrical Specifications

Amperage : 15 A

Current Interrupting : Certified for current interrupting at full rated current

Dielectric Voltage Withstand : 2000V minimum per UL 498

Grounding : Self-Grounding

Maximum Working Voltage : 125V as rated

Pole : 2

Temperature Rise : Max 30C after 100 cycles OL at 150 percent rated current

Voltage : 125 VAC

Wire : 3

Environmental Specifications

Flammability : Rated V-2 per UL 94

Operating Temperature : -40° C to 60°C

Material Specifications

Base Material : Polycarbonate

Bushing : Die Cast Aluminum

Color : White

Cover Material : Thermoplastic

Ground Clips : Brass

Grounding Screw : Plated Steel

Mounting Screws : Triple Combination Head, Steel

Mounting Strap : Galvanized Steel with Riveted Ground Contacts

Power Contacts : Brass, triple wipe

Terminal Leads : 6", #12 AWG THHN

Mechanical Specifications

Lead Identification : Leads identified in accordance with UL 498 (black, white & green)

Product ID : Ratings are permanently marked on device

Termination : Pre-Wired Leads (hot and neutral)

Product Features

Color : White

Device Type : Duplex Receptacle Outlet

Feature 4 : Smooth Face

Grade : Commercial Specification Grade

NEMA : 5-15R

Standards and Certifications

ANSI : C-73

CSA C22.2 No. 42 : File 152105


NEMA : WD-6

NOM : 057

UL498 : File E13399

Warranty : 10-Year Limited

Wiring Diagram



SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/>
JOB NUMBER: <input type="text"/>	<input type="text"/>

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·
FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52) 5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.