

68W47

Wetguard Watertight Locking Inlet

30 Amp, 125 Volt, NEMA L5-30 , 2P, 3W, Single Locking Inlet with IP66 Rated Cover, Industrial Grade, Grounding, Corrosion Resistant, Wetguard - YELLOW



UPC Code : 078477519332

Country Of Origin : Mexico

NEMA :  L5-30P

- BATTLE THE ELEMENTS- Resistant to water, acids, alkalis, and many automotive and industrial lubricants and solvents.
- ADVANCED LID DESIGN- Our spring-loaded flip lid is impact and chemical resistant with a Valox® PBT cover
- MORE SECURE- Dual-hasp provides additional lockout /tagout option for added security.
- DURABLE- Ideal for harsh environments with added resistance against heat, chemical corrosion, and physical abrasion

Technical Information

Electrical Specifications

Amperage : 30 A

Current Limiting : Full Rated Current

Dielectric Voltage :
Withstands 2000V per UL498

Grounding : Grounding

Pole : 2

Temperature Rise : Max 30C
after 250 cycles OL at 200
percent rated current

Voltage : 125 VAC

Wire : 3

Environmental Specifications

Enclosure Rating : NEMA 4,
4X, 12 IEC IP66

Environment : Wet

Flammability : Rated V-2 per
UL 94 (wiring module)

Operating Temperature : -40°
C to 60°C

Material Specifications

Blades/Contacts, Terminal Clamps : Electroless Nickel-coated Brass

Cover Gasket : Santoprene
TPV

Cover/Lid : Valox PBT

Mounting and Assembly

Screws : Stainless steel, non-magnetic

Terminal Screws : Electroless
Nickel-coated Brass

Torsion Spring Mechanism (Flip Lids) : Stainless Steel

Wiring Module : Nylon

Mechanical Specifications

Product ID : Ratings and
NEMA I.D. permanently marked
on device

Screw Terminal Torque : 12-
14 in-lbs

Terminal Accom. : #12 AWG
to #8 AWG

Wiring Module Mounting Cup
: Valox PBT

Product Features

Brand : Wetguard

Color : Yellow

Device Type : Locking Inlet

NEMA : L5-30P

Standards and Certifications

ANSI : C-73

CSA : C22.2 No. 42

NEMA : WD-6

NOM : 057

UL : 498

Warranty : Limited Lifetime
Warranty

SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/>
JOB NUMBER: <input type="text"/>	<input type="text"/>

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)

5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.