

# B2120-B

Type 2 Surge Protective Device, 120/240 VAC, Split Phase



B Series Type 2 Surge Panel, 120/240 VAC, Split Phase, Max Surge Current Rating of 65kA per Mode/130kA per Phase, 200kA Short Circuit Current Rating (SCCR), 20kA I-nominal ( $I_n$ ) Rating, NEMA 4X Rated Enclosure, Thermally Protected MOVs, VPR Performance Data = L-N: 700, L-G: 700, N-G: 700, L-L: 1200, Maximum Continuous Operating Voltage (MCOV): 180V/360V, Plastic Enclosure, LED Status Monitoring, Audible Alarm, UL 1449 Listed, UL 1283 EMI/RFI Filtering, Approximate Lead Length = 18"

UPC Code : 07847758304

Country Of Origin : Please Contact Customer Service

- Leviton surge protective devices (SPDs) divert damaging voltage transients, or surges, away from electronic equipment
- Ideal for the branch panel in COMMERCIAL AND INDUSTRIAL APPLICATIONS and the main panel in light commercial applications, the B Series is versatile in its usage
- Code Compliant – in 2020, Article 230.67 of the National Electrical Code® (NEC) updates required all services supplying dwelling units to be provided with a surge protective device (SPD), as an integral part of equipment or located immediately adjacent. **The SPD must be a Type 1 or Type 2 SPD.** The 2023 code expanded the requirements to dormitory units, guest rooms and guest suites of hotels and motels, and areas of nursing homes and limited-care facilities used exclusively as patient sleeping rooms

## Technical Information

### Electrical Specifications

**Connection Type** : #12 AWG

**Frequency** : 50/60Hz

**MCOV** : 180V

**Recommended Circuit Breaker Rating** : 20A

**Short Circuit Current Rating** : 200kA

**Surge Technology** : Thermally Protected MOVs

**Type** : 2

**Voltage Configuration** : 120 /240 VAC/CA Split Phase

### Enclosure

**Color** : Gray

**Connector** : 3/4" NPT Side Mount Nipple

**Dimensions** : 7.95" x 3.06" x 2.75"

**Enclosure Material** : Polycarbonate

**Mount** : Surface

**NEMA Rating** : NEMA 4X

### Environmental Specifications

**Humidity Range** : 0 to 95% Non-Condensing

**Storage Temperature** : -49°F to 140°F (-45°C to 60°C)

### Performance Data

**Nominal Discharge Current Rating** : 20kA

**Remote Monitoring** : Form C Dry Contacts, 240V, 2A

**VPR L-G** : 700.0

**VPR L-L** : 1200.0

**VPR L-N** : 700.0

**VPR N-G** : 700.0

Product Features

**Disconnect Switch** : No

**Filtering** : Yes

**Replaceable Modules** : No

**Surge Counter** : No

Standards, Certifications & Compliance

**ANSI/IEEE** : C-62.41.1-2002, C-62.41.2-2002 C-62.45-2002

**CSA** : CSA C22.2 No. 269.1-17, 2017-02

**California Prop 65** : Compliant

**RoHS** : Compliant

**Series** : B Series

**UL** : 1449 5th Edition: 2021, cULus

Warranty

**Warranty** : 5-Year Limited

**Patents** \*

N\_A

This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

**Leviton Manufacturing Co., Inc**

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S. T. Monday-Friday): +1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52) 5386- 1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

**Visit our Website at: [www.leviton.com](http://www.leviton.com)**

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to: [www.leviton.com/international/contacts](http://www.leviton.com/international/contacts)

**© 2024 Leviton Manufacturing Co., Inc.**