



Color :  Ivory

UPC Code : 078477730935

Country Of Origin : China

NEMA :  5-20R

Available Colors :



G5362-WTI

20 Amp SmartlockPro® GFCI Receptacle/Outlet, Industrial Grade, Weather and Tamper-Resistant

SmartlockPro GFCI Duplex Receptacle Outlet, Extra Heavy-Duty Industrial Specification Grade, Weather and Tamper-Resistant, Power Indication, 20 Amp, 125 Volt, Back or Side Wire, NEMA 5-20R, 2-Pole, 3-Wire, Self-Grounding - Ivory

Peace of mind, all the time. The SmartlockPro Self-Test GFCI tests itself even if you forget. Designed to meet the latest UL standard for auto-monitoring (self-test) our complete line of self-test GFCIs periodically conduct an automatic internal test to confirm that it can respond to a ground fault. With the slimmest profile on the market, the device allows for fast and easy installation, while Leviton's patented reset lockout mechanism prevents reset of the GFCI if it is not wired or operating correctly. The SmartlockPro Self-Test GFCI is the smart choice in ground fault circuit interrupter protection.

Technical Information

AC Horsepower Ratings

At Rated Voltage : 1 HP

Electrical Specifications

Amperage : 20 A

Grounding : Self-Grounding

Pole : 2

Short Circuit Current Rating : 10kA

Voltage : 125 VAC

Wire : 3

Environmental Specifications

Flammability : Rated V-0 per UL 94

Operating Temperature : -35C to +66C

Material Specifications

Body Material : Polycarbonate

Face Material : PBT

Ground Clips : Brass

Grounding Screw : Stainless Steel

Line Contacts : Brass

Shutter Mechanism : Delrin® Acetal

Strap Material : Nickel Plated Steel

Terminal Clamp : Brass

Terminal Screws : Stainless Steel

Mechanical Specifications

Product ID : Ratings are permanently marked on device

Product Features

Brand : SmartlockPro

Screw Terminal Torque : 14-18 in-lbs

Terminal Accom. : 14-10 AWG solid or stranded

Terminal ID : Black-Hot, White-Neutral, Green-Ground

Termination : Back or Side Wire

Color : Ivory

Device Type : Duplex Receptacle Outlet

Function : GFCI

Grade : Extra Heavy-Duty Industrial Specification Grade

NEMA : 5-20R

Standards and Certifications

ANSI : C-73

Applicable Standards : UL 943, UL 498, CSA C22.2 No. 42 & 144, FedSpec W-C-596

Certification/Listing : UL, CSA, NOM-ANCE

NEMA : WD-1 & WD-6

Warranty

Warranty : 2-Year Limited

Patents *

CA2425810	CA2425810
CA2427366	CA2427366
CA2515035	CA2515035
CA2621644	CA2621644
CA2677283	CA2677283
CA2865659	MX251584
MX251584	MX269232
MX269232	MX276626
MX276626	MX302458
MX302458	MX308495
MX308495	MX315596
US7355117	US7355117
US7697252	US7697252
US7737809	US7737809
US7820909	US7820909
US7868719	US7868719
US8004804	US8004804
US8242362	US8242362
US8547126	US8587914
US8587914	US8599522
US8599522	US9053886
US9053886	US9077091

This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

SPECIFICATION SUBMITTAL

JOB NAME:

CATALOG NUMBERS:

JOB NUMBER:		

Leviton Manufacturing Co., Inc
201 North Service Road, Melville, NY 11747
Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.
165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·
FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.
Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com
© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without
notice.

Leviton has a global presence.
If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.