



Color :  White

UPC Code : 078477999967

Country Of Origin : China

NEMA :  5-15R

GUSB1-W

15A SmartlockPro® GFCI Combination 24W(4.8A) Type A USB In-Wall Charger Outlet

15 Amp, 125 Volt Receptacle/Outlet, 20 Amp Feed-Through, Tamper-Resistant, SmartlockPro® Self-Test GFCI Combination Type A USB In-Wall Charger, Wire Leads, NEMA 5-15R, 24W (4.8 Amps), Dual Type-A/A USB Chargers, screws and self-grounding clip included - White

- SAFE - Delivers continuous ground fault protection, automatically self-tests to ensure it can respond to a ground fault
- FAST CHARGING - Smart chip technology provides over 2X the charging power of other GFCI USB outlets for a faster charge
- CODE REQUIRED - Fulfill NEC® requirements anywhere GFCI protection is needed
- SIMPLE - Status indicator light provides simple, intuitive feedback
- INSTALL - Requires extra deep wallbox for installation

Technical Information

AC Horsepower Ratings

At Rated Voltage : 1 HP

Dielectric Voltage :

Withstands 1250VAC per UL 943 and CSA-C22.2 No. 144.1-06

Temperature Rise : Max 30C after 100 cycles OL at 150 percent rated current

Environmental Specifications

Flammability : UL94, 5VA

Operating Temperature : -10° C to 40°C

Electrical Specifications

Grounding : Self-Grounding

Ratings : 15A - 125V, 4.8A @ 5V

Temperature Rise : Max 30C after 100 cycles OL at 150 percent rated current

Voltage : 125 VAC

Material Specifications

Body Material : Thermoplastic

Color : White

Cover Material : Thermoplastic

Face Material : Thermoplastic

Grade : Residential /Commercial Specification Grade

Line Contacts : Brass Double Wipe .031 Thick

Product ID : Stamped on Strap

Strap Material : Galvanized Steel

Terminal ID : Green lead - GND. Line and load both have: Black lead - Hot, White lead - Neutral

Mechanical Specifications

Pole : 2
Tamper Resistant : Yes
Torque Range : 14-18 lbs.
Type : GFCI/USB Combination
Voltage : 125 VAC
Wire : 5

Product Features

Amperage : 15 A
At Rated Voltage : 1 HP
Brand : SmartlockPro
Color : White
Feature : Self-Test
Flammability : UL94, 5VA
Grade : Residential
/Commercial Specification
Grade
Grounding : Self-Grounding
Pole : 2
Product Type : GFCI/Outlet
/USB Combo
Tamper Resistant : Yes
Termination : Wire leads
(12AWG)
Trip Level : Class A, 5mA plus
or minus 1mA
Type : GFCI/USB Combination
Voltage : 125 VAC
Wallplate : Not Included
Warranty : 2-Year Limited
Wire : 5

Standards & Certifications

ANSI : Yes
CSA C22.2 No. 42 : Yes
CSA-C22.2 No. 144.1-06 : Yes
FCC Part 15 : Class B
Fed Spec WC-596 : No
Listed : cCSAus
NOM : Yes
UL 1310 : Yes
UL 498 : Yes
Warranty : 2-Year Limited

Patents*

CA2427366
CA2621644
CA2677283
MX251584
MX276626
MX308495

CA2515035
CA2624409
CA2730014
MX269232
MX302458
MX344697

US10483066	US7355117
US7697252	US7737809
US7820909	US7868719
US8004804	US8242362
US8587914	US9053886
US9276393	

This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

SPECIFICATION SUBMITTAL

JOB NAME: 	CATALOG NUMBERS: 	
JOB NUMBER: 		

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)

5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.