



Color : ☐ White

UPC Code : 078477654897

Country Of Origin : China

Available Colors :



Ivory



Light Almond

IPHS5-1LW

Decora In-Wall Humidity Sensor & Fan Control, 3A, Residential Grade, Single Pole

Humidity Sensor and Fan Control, Single Pole, 600W Incandescent, 150W LED/CFL, 400VA Inductive/Ballast, 1/6th HP Motor, Wallplate/Faceplate not included, White

DISCONTINUED

Suggested Replacement SKUs: :

ROHS Compliant : Yes

The Leviton Humidity Sensor and Fan Control automatically detects excess humidity in a room and activates the ventilation fan to lessen condensation which helps reduce mold and mildew. The sensor uses a microprocessor combined with state-of-the-art digital sensing technology to continuously monitor and manage humidity levels in areas of the home prone to condensation and mildew. It features user-friendly controls to adjust sensitivity, humidity level and time-out settings. The sensor can replace a single pole switch and can be used with most bathroom or ventilation fans or fan/light combinations. It is designed to fit within a standard wallbox and requires a neutral wire for operation. Contemporary in design, the Humidity Sensor and Fan Control is the ideal solution for controlling ventilation in areas of high humidity, dampness or rooms prone to condensation and mildew such as: Bathrooms, Basements, Laundry Rooms and Home Spas. The sensor also helps reduce energy usage by automatically operating the fan only when needed to control excess humidity.

Technical Information

Control Specifications

Time Adjustment : 10m-45m

Input Characteristics

Adjustment : Manual

Electrical Specifications

Ground Connection : No

Load Rating : 600W
Incandescent, 150W LED/CFL,
400VA Inductive/Ballast, 1/6th
HP Motor

Neutral : Required

Pole : 1

Power Consumption : <0.5
Watts

Switch Type : Single-Pole

Time Delay : 10m-45m

Voltage : 120 VAC

Material Specifications

Color : White

Dimensions : W 1.75" X D
1.22" X H 4.13"

LED Color : Green

Product Features

Color : White

LED Color : Green

Style Name : Decora

Torque Range : 14 – 18 in.-lbs

Wallplate : Order Separately

Warranty : 5-Year Limited

Standards and Certifications

2016 CALGREEN : Yes

ASHRAE : Yes

California Title 24 : Yes

Standards and Certifications : CUL/US

Warranty

Warranty : 5-Year Limited

Features and Benefits

- Automatically detects excess humidity in a room and activates the ventilation fan to lessen condensation which helps reduce mold and mildew
- Sensor uses microprocessor and digital sensing technology to continuously monitor and manage humidity levels in a room
- Built-in timer sets the “minimum ON time” for the ventilation fan. The sensor time settings can be custom set to 10, 20, 30 or 45 minute intervals. The sensor will continue to operate the fan for the minimum time set or until there is a reduction in room humidity level
- A sensitivity level adjustment allows users to adjust the sensor’s sensitivity to ambient air to prevent false cycling
- Features an Air Cycle mode which automatically turns ON the ventilation fan for a set period of time and repeats the cycle hourly (eg. 20 minutes ON/40 minutes OFF each hour)
- Replaces a single pole switch for control of ventilation fan or a fan/light combination
- Fits in a standard wall box and requires a neutral for operation
- Can be used to comply with 2019 CALGREEN, Part II, Indoor Air Quality and Exhaust.
- Can be used to comply with the requirements of 2019 California Title 24, Part 6 Indoor Air Quality and Mechanical Ventilation
- Meets the requirements of ASHRAE 62.2
- Five-Year Limited warranty

Patents *

US9976764

USD706726

This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

SPECIFICATION SUBMITTAL

JOB NAME:

CATALOG NUMBERS:

<div></div>	<div></div>	<div></div>
JOB NUMBER:	<div></div>	<div></div>
<div></div>		

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747
Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·
FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without
notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.