

# N7899-KT



**UPC Code :** 07847756100

**Country Of Origin :** China

**NEMA :**  5-20R

20 Amp SmartlockPro® GFCI Receptacle/Outlet

20 Amp, 125 Volt Receptacle, 20 Amp Feed-Through, SmartLock Pro Slim GFCI, monochromatic, back and side wired, self grounding clip included , bulk-pack, wallplate sold separately - Light Almond

## DISCONTINUED

Suggested Replacement SKUs: :

Slim is in. New SmartlockPro Slim GFCIs Install Easily Industry-leading quality, professional grade lockout action, and the slimmest profile on the market make SmartlockPro Slim GFCIs the smartest choice in ground fault circuit interrupter protection. Faster and easier to install in any wallbox because depth is reduced, the slim GFCIs flush mount to the wall with minimal protrusion for a sleek, finished look. Enhanced features include external back wiring for positive indication the wire is properly seated, exceptional resistance to wire pullout and the ability to withstand high torque.

## Technical Information

### AC Horsepower Ratings

**At Rated Voltage :** 1 HP

#### **Dielectric Voltage :**

Withstands 1250VAC per UL 943 and CSA-C22.2 No. 144.1-06

**Short Circuit Current Rating :** 10KA

**Temperature Rise :** Max 30C after 100 cycles OL at 150 percent rated current

### Electrical Specifications

#### **Dielectric Voltage :**

Withstands 1250VAC per UL 943 and CSA-C22.2 No. 144.1-06

**Flammability :** Rated V-2 per UL 94

**Operating Temperature :** -35C to +66C

**Short Circuit Current Rating :** 10KA

**Temperature Rise :** Max 30C after 100 cycles OL at 150 percent rated current

### Environmental Specifications

**Body Material :** Polycarbonate

**Clamps :** Brass

**Face Material :** Thermoplastic

**Flammability :** Rated V-2 per UL 94

**Grounding Screw :** Plated Steel

**Line Contacts :** Brass Triple Wipe .031 Thick

### Material Specifications

**Body Material :** Polycarbonate

**Clamps :** Brass

**Face Material :** Thermoplastic

**Grounding Screw :** Plated Steel

**Line Contacts :** Brass Triple Wipe .031 Thick

**Notes :** Wallplate Sold Separately

**Notes :** Wallplate Sold Separately

**Operating Temperature :** -35C to +66C

**Terminal Screws :** Plated Steel

**Yoke :** Zinc-Plated Steel

**Product ID :** Ratings are permanently marked on device

**Terminal Accom. :** 14-10 AWG

**Terminal ID :** Brass-Hot, Green-Ground, Silver-Neutral

**Terminal Screws :** Plated Steel

**Yoke :** Zinc-Plated Steel

Mechanical Specifications

**Amperage :** 20 A

**Body Material :** Polycarbonate

**Color :** Light Almond

**Face Material :** Thermoplastic

**Feature :** SmartlockPro® Slim

**Fed Spec WC-596 :** Yes

**Grounding :** Self-Grounding

**NEMA :** 5-20R

**Notes :** Wallplate Sold Separately

**Pole :** 2

**Product ID :** Ratings are permanently marked on device

**Standards and Certifications :** UL/CSA

**Strap Material :** Galvanized Steel

**Terminal Accom. :** 14-10 AWG

**Terminal ID :** Brass-Hot, Green-Ground, Silver-Neutral

**Termination :** Back & Side

**Trip Level :** Class A, 5mA plus or minus 1mA

**Voltage :** 125 VAC

**Warranty :** 2-Year Limited

**Wire :** 3

Standards and Certifications

**ANSI :** C-73

**CSA C22.2 No. 42 :** Yes

**CSA-C22.2 No. 144.1-06 :** File LR-57811

**Fed Spec WC-596 :** Yes

**MIL-SPEC :** A-A-55459-SB

**NEMA :** WD-6

**NOM :** 057

**UL 943 :** File E48380

Product Features

**Amperage :** 20 A

**At Rated Voltage :** 1 HP

**Color :** Light Almond

**Feature :** SmartlockPro® Slim

**Fed Spec WC-596 :** Yes

**Grounding :** Self-Grounding

**NEMA :** 5-20R

**Pole :** 2

**Standards and Certifications :** UL/CSA

**Strap Material :** Galvanized Steel

**Termination :** Back & Side

**Trip Level :** Class A, 5mA plus or minus 1mA

**Type :** Non-Tamper Resistant

**Voltage :** 125 VAC

**Warranty :** 2-Year Limited

**Wire :** 3

UL498 : Yes

**SPECIFICATION SUBMITTAL**

<b>JOB NAME:</b> <input type="text"/>	<b>CATALOG NUMBERS:</b> <input type="text"/>	<input type="text"/>
<b>JOB NUMBER:</b> <input type="text"/>	<input type="text"/>	<input type="text"/>

**Leviton Manufacturing Co., Inc**

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)

5386- 1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

**Visit our Website at: [www.leviton.com](http://www.leviton.com)**

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to:

[www.leviton.com/international/contacts](http://www.leviton.com/international/contacts)

© 2024 Leviton Manufacturing Co., Inc.