

# N7899-DIN



**Color:**  Black

**UPC Code:** 07847761306

**Country of Origin:** China

**NEMA:** 5-20R



## Brand Features

Leviton is the leading manufacturer of Ground Fault Circuit Interrupters (GFCIs) in the electrical industry. Available in Extra Heavy Duty Hospital and Commercial Spec Grade, they are ideal for a wide range of GFCI applications. Our large selection of GFCIs includes Tamper-Resistant (TR) GFCI devices that meet Section 406.11 of the 2008 code and help protect children from electrical shock. For the highest level of ground fault protection, install 2008 NEC code compliant Weather-Resistant GFCI (WR) receptacles, which meet UL 498 requirements. Built with UV stabilized engineering thermoplastic, the devices have high cold impact resistance and feature stainless steel straps and mounting screws.

## Item Description

20 Amp, 125 Volt, NEMA 5-20R, DIN Rail Mount SmartlockPro® GFCI Duplex Receptacle

## Technical Information

AC Horsepower Ratings

**At Rated Voltage:** 1 HP

Electrical Specifications

**Amperage:** 20 Amp

**Voltage:** 125 Volt

Environmental Specifications

**Flammability:** Rated V-0 per UL94

**Operating Temperature:** -35C to 65C

**Storage Temperature:** -20°C to 85°C

Material Specifications

**Enclosure Material:** Polycarbonate

**Enclosure Cover Material:** Polycarbonate

**Line Contacts:** Nickel-Plated Brass

**Face Material:** Polyester

Mechanical Specifications

**Terminal Accom.:** 14-10 AWG

**Product ID:** Markings are permanently marked on device

Performance Data

**Short Circuit Current Rating:** 10kA

**Diagnostics:** Indicator Light

**Trip Level:** Class A, 5mA plus or minus 1mA

Product Features

**Feature:** SmartLockPRO

**NEMA:** 5-20R

**Color:** Black

Standards and Certifications

**UL 943:** File E48380

**NEMA:** WD-1 & WD-6

**ANSI:** C-73

**Fed Spec WC-596:** Yes

Warranty

**Warranty:** 2-Year Limited

## SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
<input type="text"/>	<input type="text"/>	<input type="text"/>
JOB NUMBER:	<input type="text"/>	<input type="text"/>

**Leviton Manufacturing Co., Inc.**

201 North Service Road, Melville, NY 11747

Telephone: 1-800-323-8920 · FAX: 1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): 1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: 1-800-469-7890 ·

FAX: 1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

**Visit our Website at: [www.leviton.com](http://www.leviton.com)**

© 2012-2014 Leviton Manufacturing Co., Inc. All rights reserved. Subject to change without notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to: [www.leviton.com/international/contacts/](http://www.leviton.com/international/contacts/)

