



Zenit

The essence of design




- Premium modular light switch range
- Multi-standard: fitting in European, American and Italian boxes
- Eco-designed
- More than 100 functions in four finishes

Zenit

Signaling and lighting systems

Color	Article-No.	Order-No.	Pack/Qty
 LED white signaling light - 1M Rated voltage: 127-230 Vac / 50-60 Hz. Lamp: white LED. Luminous flux: > 2 lumen at 1 meter. White diffuser.			
White	N2180 BL	2CLA218000N1101	5
 LED warm white signaling light - 1M Rated voltage: 127-230 Vac / 50-60 Hz. Lamp: white LED. 2.700 Kelvin. Low luminous flux: < 0,5 lumen at 0,3 meter. White diffuser.			
White	N2180.1 BL	2CLA218010N1101	5
 LED signaling light - 2M Rated voltage: 127-230 Vac / 50-60 Hz. Lamp: white LED. Luminous flux: > 2 lumen at 1 meter. White diffuser.			
White	N2280 BL	2CLA228000N1101	1
 LED DND/MUR signaling light - 2M Rated voltage: 127-230 Vac / 50-60 Hz. Lamp: red/green LED. Luminous flux: > 2 lumen at 1 meter. White diffuser.			
White	N2280.2 RJ/VD	2CLA228020N1101	1
 Labels for signaling / beacon lights - 2M Labels with symbols for signaling and beacon lights code: N2280, N2280.2 & N2281. Symbols: "WC men", "WC women", "No smoking", "Direction", "WC handic.", "WC", "Salida" and no symbol label.			
	N2281.1	2CLA228110N1001	5

Color	Article-No.	Order-No.	Pack/Qty
 LED red signaling light - 1M Rated voltage: 127-230 Vac / 50-60 Hz. Lamp: white LED. Luminous flux: > 2 lumen at 1 meter. Red diffuser.			
Red	N2180 RJ	2CLA218000N1601	5
 LED red signaling light - 1M Rated voltage: 127-230 Vac / 50-60 Hz. Lamp: white LED. Luminous flux: > 2 lumen at 1 meter. Green diffuser.			
Green	N2180 VD	2CLA218000N1801	5
 Beacon LED light - 2M Rated voltage: 230 Vac $\pm$ 10% / 50 - 60 Hz . Lamp: white LED. White diffuser. Light intensity: 2400 med. Beam angle: 120°. Autonomy: 2 hours. Battery: Ni-MH (not replaceable). Note: to be installed in boxes with 50mm depth or more.			
White	N2181 BL	2CLA218100N1101	1
 Withdrawable beacon LED light - 2M Rated voltage: 230 Vac $\pm$ 10% / 50 - 60 Hz . Lamp: white LED. White diffuser. Light intensity: 20 lumens. Beam angle: 120°. Autonomy: 2 hours. Battery: Ni-MH (not replaceable). Note: to be installed in boxes with 50mm depth or more.			
White	N2281.2 BL	2CLA228120N1101	1

Asea Brown Boveri, S.A.

Fábrica Niessen

Pol. Ind. de Aranguren, 6

20180 OIARTZUN

Spain

Tel.: +34 943 260 101

Fax: +34 943 260 240

abb.es/niessen

