


Linnea

LINNEA is a linear luminaire built with an extruded aluminium profile for suspended installation, installation mounted to the ceiling or recessed installation. It stands out thanks to its minimal design and its microprismatic diffuser which generates very homogeneous lighting with optimal visual comfort.

LINNEA es una luminaria lineal construida en perfil de aluminio extruido para instalación suspendida, adosada o empotrada a techo. Destaca por su diseño minimalista y su difusor microprismático que genera una iluminación muy homogénea con un óptimo confort visual.



Equivalent output	Potencia equivalente	Linnea (30W to/hasta 80W)
Installation	Instalación	Surface mounted Suspended Recessed Adosada a techo Suspendida a techo Empotrada a techo
Light source	Fuente de luz	LED
Photobiological safety	Seguridad fotobiológica	0
UGR	UGR	<19
Flickering < 15%	Flickering <15%	✓
CRI	CRI	80-90
MacAdam ellipse	Elipse de Macadam	3
Beam angle	Ángulo de apertura	95
Consumption (W)	Consumo (W)	20,8W 31,2W 38,4W 57,6W
Temperature	Temperatura	4000
Lumens	Lúmenes	2960 4440 5440 8160
Power factor	Factor de potencia	0,95
Useful life (h) LED	Vida útil (h) Led	60000
Useful life (h) driver	Vida útil (h) driver	>60000
Expectancy	Expectativa	L70F10
Zhaga replaceable LED	Led sustituible Zhaga	✓
Starting cycles	Ciclos de encendido	120000
DALI	DALI	✓
Continuous function 24h	Funcionamiento continuado 24h	✓
Integrated electronics	Electronica integrada	✓
IP	IP	30
Class	Clase	I
Weight (Kg)	Peso (Kg)	2,75 / 4,12



C0-C180
C90-C270
 $\eta=61\%$

- No photobiological risk.
- Light range: 2,880-8,160 lumens
- Option to make continuous strips using the joints accessory.
- UGR < 19.

- Exento de riesgo fotobiológico.
- Rango lumínico: 2.880-8.160 lm.
- Posibilidad de hacer tiras continuas mediante el accesorio de unión.
- UGR<19.

Finishes

Acabados

- White / Blanco
● Grey / Gris

Option to make continuous strips using the joints accessory

Posibilidad de hacer tiras continuas mediante el accesorio de unión

Three versions available
Tres versiones disponibles

○ Voltaje Universal 120/277V




Surface mounted
Suspendida

Adosada a techo
Suspendida

Linnea Sobreponer/Suspend

	W	K	LUMEN	COLOR	L(mm)	Icon
LED LI4H4UOB	1x38,4W	4000	5440 lm	○	1125	2,75
LED LI4H4UOG	1x38,4W	4000	5440 lm	●	1125	2,75
LED LI4L4UOB	1x20,8W	4000	2960 lm	○	1125	2,75
LED LI4L4UOG	1x20,8W	4000	2960 lm	●	1125	2,75




Recessed

Empotrada a techo


Linnea Empotrar

	W	K	LUMEN	COLOR	L(mm)	Icon
LED LE4H4UOB	38,4W	4000	5440 lm	○	1125	2,9
LED LE4H4UOG	38,4W	4000	5440 lm	●	1125	2,9
LED LE4L4UOB	20,8W	4000	2960 lm	○	1125	2,9
LED LE4L4UOG	20,8W	4000	2960 lm	●	1125	2,9




Accesorio de suspensión

	L (m)
1029L2	2
1029L4	4




Tapa final

	COLOR
LI016G	●
LI016B	○




Accesorio de instalación

	COLOR
ETC1029G	●
ETC1029B	○



Tapa final versión empotrada

	COLOR
LE016G	●
LE016B	○



Accesorio de unión

	COLOR
LI014	○

