




LÁMPARAS FLUORESCENTES COMPACTAS PIN BASE




ESPECIFICACIONES

Vida: 12 000-20 000 hrs.

CFL Pin Base DULUX DE

Clave	Descripción	Potencia [W]	Flujo Luminoso Inicial [lm]	MOL [mm]	IRC	CCT [K]	Bulbo	Tipo de Base	Vida Promedio [h]	Estatus	Piezas por Caja
20671	CF13DDE835ECO	13	900	114	82	3 500	D	G24q-1	20 000	MTS	50
20121	CF13DDE841ECO	13	900	114	82	4 100	D	G24q-1	12 000	MTS	50
20683	CF18DDE827ECO	18	1 150	130	82	2 700	D	G24q-2	20 000	MTS	50
20668	CF18DDE841ECO	18	1 150	130	82	4 100	D	G24q-2	20 000	MTO	50
20123	CF26DD/E/827/ECO	26	1 710	150	82	2 700	D	G24q-3	12 000	MTS	50
20124	CF26DDE835ECO	26	1 710	150	82	3 500	D	G24q-3	12 000	MTS	50
20125	CF26DDE841ECO	26	1 710	150	82	4 100	D	G24q-3	12 000	MTS	50



ESPECIFICACIONES

Vida: 16 000 hrs.

CFL Pin Base DULUX TE

Clave	Descripción	Potencia [W]	Flujo Luminoso Inicial [lm]	MOL [mm]	IRC	CCT [K]	Bulbo	Tipo de Base	Vida Promedio [h]	Estatus	Piezas por Caja
20880	CF26DTEIN830ECO	26	1 800	126	82	3 000	T	GX24q-3	16 000	MTS	50
20881	CF26DTEIN835ECO	26	1 800	126	82	3 500	T	GX24q-3	16 000	MTO	50
20882	CF26DTEIN841ECO	26	1 800	126	82	4 100	T	GX24q-3	16 000	MTO	50
20054	CF32DTEIN830ECO	32	2 400	142	82	3 000	T	GX24q-3	16 000	MTS	50
20055	CF32DTEIN835ECO	32	2 400	142	82	3 500	T	GX24q-3	16 000	MTO	50
20056	CF32DTEIN841ECO	32	2 400	142	82	4 100	T	GX24q-3	16 000	MTS	50
20888	CF42DTEIN830ECO	42	3 200	163	82	3 000	T	GX24q-4	16 000	MTS	50
20871	CF42DTEIN835ECO	42	3 200	163	82	3 500	T	GX24q-4	16 000	MTS	50
20890	CF42DTEIN841ECO	42	3 200	163	82	4 100	T	GX24q-4	16 000	MTS	50