


LÁMPARAS FLUORESCENTES LINEALES



ESPECIFICACIONES

Vida: 22 000-24 000 hrs.

PENTRON® T5 ALTA EFICIENCIA (HE)

Clave	Descripción	Potencia [W]	Flujo Luminoso Inicial [lm]	MOL [mm]	IRC	CCT [K]	Bulbo	Tipo de Base	Vida Promedio [h]	Estatus	Piezas por Caja
85000	PENTRON FH14/830 BC	14	1 350	563	>80	3 000	T5	G5	24 000	MTS	20
85001	FP14841ECO	14	1 200	563	>80	4 100	T5	G5	24 000	MTS	40
85100	FP14/865/ECO	14	1 300	563	>80	6 500	T5	G5	24 000	MTS	40
85101	FP21/830/ECO	21	2 100	863	>80	3 000	T5	G5	24 000	MTS	40
85102	FP21/841/ECO	21	2 100	863	>80	4 000	T5	G5	24 000	MTS	40
85103	FP21/865/ECO	21	2 000	863	>80	6 500	T5	G5	24 000	MTS	40
85105	FP28830ECO	28	2 600	1 163	>80	3 000	T5	G5	24 000	MTS	40
85104	FP28835ECO	28	2 600	1 163	>80	3 500	T5	G5	24 000	MTS	40
85106	FP28841ECO	28	2 600	1 163	>80	4 100	T5	G5	24 000	MTS	40
85107	FP28865ECO	28	2 600	1 163	>80	6 500	T5	G5	30 000	MTS	40
82218	FH28W/880 HE SKYWHITE	28	2 690	1 163	>80	8 800	T5	G5	22 000	MTO	20
88129	PENTRON FH28W/60 ROJO HE	28	2 200	1 163	---	6 000	T5	G5	22 000	MTO	10
88130	PENTRON FH28W/66 VERDE HE	28	3 700	1 163	---	6 600	T5	G5	22 000	MTO	10
88128	PENTRON FH28W/67 AZUL	28	750	1 163	---	6 700	T5	G5	22 000	MTS	10
82332	PENTRON FH35/830 BC	35	3 650	1 463	>80	3 000	T5	G5	22 000	MTS	40
82333	PENTRON FH35/840 BF	35	3 650	1 463	>80	4 000	T5	G5	22 000	MTS	40
82334	PENTRON FH35/865 LDD	35	3 450	1 463	>80	6 500	T5	G5	22 000	MTS	40