


LÁMPARAS FLUORESCENTES LINEALES



ESPECIFICACIONES

Vida: 22 000-24 000 hrs.

PENTRON® T5 ALTA EFICIENCIA (HE)

Clave	Descripción	Potencia [W]	Flujo Luminoso Inicial [lm]	MOL [mm]	IRC	CCT [K]	Bulbo	Tipo de Base	Vida Promedio [h]	Estatus	Piezas por Caja
85000	PENTRON FH14/830 BC	14	1 350	563	>80	3 000	T5	G5	24 000	MTS	20
85001	FP14841ECO	14	1 200	563	>80	4 100	T5	G5	24 000	MTS	40
85100	FP14/865/ECO	14	1 300	563	>80	6 500	T5	G5	24 000	MTS	40
85101	FP21/830/ECO	21	2 100	863	>80	3 000	T5	G5	24 000	MTS	40
85102	FP21/841/ECO	21	2 100	863	>80	4 000	T5	G5	24 000	MTS	40
85103	FP21/865/ECO	21	2 000	863	>80	6 500	T5	G5	24 000	MTS	40
85105	FP28830ECO	28	2 600	1 163	>80	3 000	T5	G5	24 000	MTS	40
85104	FP28835ECO	28	2 600	1 163	>80	3 500	T5	G5	24 000	MTS	40
85106	FP28841ECO	28	2 600	1 163	>80	4 100	T5	G5	24 000	MTS	40
85107	FP28865ECO	28	2 600	1 163	>80	6 500	T5	G5	30 000	MTS	40
82218	FH28W/880 HE SKYWHITE	28	2 690	1 163	>80	8 800	T5	G5	22 000	MTO	20
88129	PENTRON FH28W/60 ROJO HE	28	2 200	1 163	---	6 000	T5	G5	22 000	MTO	10
88130	PENTRON FH28W/66 VERDE HE	28	3 700	1 163	---	6 600	T5	G5	22 000	MTO	10
88128	PENTRON FH28W/67 AZUL	28	750	1 163	---	6 700	T5	G5	22 000	MTS	10
82332	PENTRON FH35/830 BC	35	3 650	1 463	>80	3 000	T5	G5	22 000	MTS	40
82333	PENTRON FH35/840 BF	35	3 650	1 463	>80	4 000	T5	G5	22 000	MTS	40
82334	PENTRON FH35/865 LDD	35	3 450	1 463	>80	6 500	T5	G5	22 000	MTS	40

ESPECIFICACIONES
Vida: 24 000-40 000 hrs.

PENTRON® T5 ALTO FLUJO (HO)

Clave	Descripción	Potencia [W]	Flujo Luminoso Inicial [lm]	MOL [mm]	IRC	CCT [K]	Bulbo	Tipo de Base	Vida Promedio [h]	Estatus	Piezas por Caja
82294	PENTRON FQ24/830 BC	24	2 000	563	>80	3 000	T5	G5	30 000	MTS	20
82295	PENTRON FQ24/840 BF	24	2 000	563	>80	4 000	T5	G5	30 000	MTS	20
82296	PENTRON FQ24/865 LDD	24	1 900	563	>80	6 500	T5	G5	30 000	MTS	20
82335	PENTRON FQ39/830 BC	39	3 500	863	>80	3 000	T5	G5	30 000	MTO	20
82336	PENTRON FQ39/840 BF	39	3 500	863	>80	4 000	T5	G5	30 000	MTS	20
*82337	PENTRON FQ39/865 LDD	39	3 325	863	>80	6 500	T5	G5	30 000	MTS	20
85108	FP54830HOECO	54	5 000	1 163	>80	3 000	T5	G5	40 000	MTS	40
85109	FP54835HOECO	54	5 000	1 163	>80	3 500	T5	G5	40 000	MTO	40
85110	FP54841HOECO	54	5 000	1 163	>80	4 100	T5	G5	40 000	MTS	40
85111	FP54850HOECO	54	4 900	1 163	>80	5 000	T5	G5	40 000	MTS	40
85112	FP54865HOECO	54	4 750	1 163	>80	6 500	T5	G5	40 000	MTS	40
81351	PENTRON FQ54/880 SKYWHITE	54	4 500	1 163	>80	8 000	T5	G5	30 000	MTO	20
*83769	PENTRON FQ54W/60 ROJO HO	54	3 650	1 163	---	Rojo	T5	G5	24 000	MTO	10
*83770	PENTRON FQ54W/66 VERDE HO	54	6 065	1 163	---	Verde	T5	G5	24 000	MTO	10
*83771	PENTRON FQ54W 67/AZUL	54	1 475	1 163	---	Azul	T5	G5	24 000	MTO	10
82149	PENTRON FQ80/830 BC	80	7 000	1 463	>80	3 000	T5	G5	30 000	MTO	20
82200	PENTRON FQ80/840 BF	80	7 000	1 463	>80	4 000	T5	G5	30 000	MTO	20
*82216	PENTRON FQ80/865 LDD	80	6 650	1 463	>80	6 500	T5	G5	30 000	MTO	20

*Disponibilidad hasta agotar inventario.

ESPECIFICACIONES
Vida: 25 000-30 000 hrs.

PENTRON® T5 ALTA EFICIENCIA SUPERSAVER (SS HE)

Clave	Descripción	Potencia [W]	Flujo Luminoso Inicial [lm]	MOL [mm]	IRC	CCT [K]	Bulbo	Tipo de Base	Vida Promedio [h]	Estatus	Piezas por Caja
21303	FP1413W830SSECO*	13	1 350	563	>80	3 000	T5	G5	25 000	MTO	40
21304	FP1413W835SSECO*	13	1 350	563	>80	3 500	T5	G5	25 000	MTO	40
21305	FP1413W841SSECO*	13	1 350	563	>80	4 100	T5	G5	25 000	MTO	40
21309	FP2826W830SSECO*	26	2 900	1 163	>80	3 000	T5	G5	30 000	MTO	40
21310	FP2826W835SSECO*	26	2 900	1 163	>80	3 500	T5	G5	30 000	MTO	40
21311	FP2826W841SSECO*	26	2 900	1 163	>80	4 100	T5	G5	30 000	MTO	40