




HCI-TF



GU6.5

ESPECIFICACIONES

Vida: 1 000 hrs.


POWERBALL® HCI - TF Base GU6.5 UV Filter

Clave	Descripción	Potencia [W]	Flujo Luminoso [lm]	Código ANSI	CCT [K]	Bulbo	Tipo de base	Vida Promedio [h]	IRC	Estatus	Piezas por Caja
* 86206	HCI -TF 20/830 WDL PB GU6,5	20	1 700	C156/E	3 000	T4	GU6.5	12 000	89	MTS	12
* 86207	HCI -TF 35W/930 WDL PB GU6,5	35	3 400	C139	3 000	T4	GU6.5	12 000	90	MTS	12

* Se discontinuará al agotar inventario



HCI-TC



G8.5

ESPECIFICACIONES

Vida: 15 000 hrs.

POWERBALL® HCI - TC Base G8.5

Clave	Descripción	Potencia [W]	Flujo Luminoso [lm]	Código ANSI	CCT [K]	Bulbo	Tipo de base	Vida Promedio [h]	IRC	Estatus	Piezas por Caja
* 86186	HCI -TC 20W/830 WDL PB G8,5	20	1 700	NA	3 000	T4.5	G8.5	15 000	83	MTS	12
86181	HCI -TC 35W/830 WDL PB G8,5	35	3 500	C139	3 000	T4.5	G8.5	15 000	85	MTS	12
86198	HCI -TC 35W/942 NDL PB G8,5	35	3 400	C139	4 200	T4.5	G8.5	15 000	90	MTS	12
86197	HCI -TC 70W/830 WDL PB G8,5	70	6 900	C98	3 000	T4.5	G8.5	15 000	89	MTS	12
86200	HCI -TC 70W/942 NDL PB G8,5	70	6 900	C98	4 200	T4.5	G8.5	15 000	96	MTS	12

* Se discontinuará al agotar inventario