



6.1 - SELLOS PARA AREAS PELIGROSAS. SERIES EYS Y EYSV. LIBRE DE COBRE.										Hoja: 3 / 4 Page:				
6.1 - SEALING FITTINGS FOR HAZARDOUS LOCATIONS. EYS AND EYSV SERIES. COPPER FREE ALUMINUM.										FICHA TECNICA / TECHNICAL DATA 007-RW-209				
USAR No. DE CODIGO PARA HACER PEDIDOS / TO ORDER USE CODE NUMBER														
Figura Figure	Catalogo Catalog	Codigo Code	Medida Hub size		Tapón / Close-up plug				Peso x 100 pzas. Weight x 100 pcs.		Pqt. Unit Pzas. Pcs.	Unit Ctn. Pzas. Pcs.	Ship Ctn. Pzas. Pcs.	
			mm	inch					kg	Lb				
	TA-2939	04.24.2939	6.35	1/4	Vaciado vertical				0.900	1.98	25			
	TA-2943	04.24.2943	12.7	1/2	Vertical filling				0.835	1.80	25		800	
	TA-2938	04.24.2938	19.0	3/4	Vaciado vert. y horiz. / Vert. & hor. filling				1.700	3.75	25		800	
	TA-2937	04.24.2937	25.4	1	Vaciado horizontal				2.720	6.00	20		600	
	TA-2636	04.24.2940	31.75	1 1/4					3.900	8.60	10		330	
	TA-2637	04.24.2941	38.1	1 1/2					5.960	13.10	10		330	
	TA-2638	04.24.2942	50.8	2					8.540	18.80	10		200	
COMPUESTO SELLADOR Y FIBRA. SEALING COMPOUND AND FIBER.  - El compuesto sellador RAWELT es usado para impedir el paso de gases, vapores o flamas de una instalación eléctrica a otra de presión atmosférica y temperatura ambiente normales. - La fibra es utilizada para crear una obstrucción para impedir escurrimientos a la tubería cuando se vierte el compuesto en el sello. - El compuesto sellador RAWELT se expande ligeramente para formar un sello completamente hermético. - Es resistente a solventes, ácidos, agua y aceites. - Tiempo de curado: 12 horas a 20°C. - The sealing compound RAWELT is used to restrict the passage of gases, vapors or flames from one portion of the electrical installation to another at atmospheric pressure and normal ambient temperatures. - The fiber is used to form a dam to restrict drains to the conduit when pour the sealing compound in the sealing fitting. - The sealing compound RAWELT expands slightly to form a seal completely hermetic. - Is resistant to solvents, acids, water and oil. - Curing time: 12 hours at 68°F.														
USAR No. DE CODIGO PARA HACER PEDIDOS / TO ORDER USE CODE NUMBER														
Figura Figure	Catalogo Catalog	Codigo Code	Peso neto del producto Net weight of product		Volumen al curar Volume when set		Unit Ctn. Pzas. Pcs.	Ship Ctn. Pzas. Pcs.	Std. Pkg. Pzas. Pcs.					
					cm ³	cu. in								
	CE-2571	04.22.2571	1 kg [*]	2.20 lb	833	50.8			10					
	FB-06	04.22.2578	60 g	2.11 oz					40					
	FB-10	04.22.2579	100 g	3.52 oz					36					
	FB-25	04.22.2580	250 g	8.81 oz					14					
	FB-50	04.22.2581	500 g	1.10 lb					5					
La presentación de 1 kg se surte con 60 g de fibra. / The container of 2 lb. includes 2 Oz. of fiber.														
NIPLES / NIPPLES														
USAR No. DE CODIGO PARA HACER PEDIDOS / TO ORDER USE CODE NUMBER														
Figura Figure	Catalogo Catalog	Codigo Code	Medida nominal Hub size		Longitud total Lenght total		Longitud de rosca Threaded lenght		Peso x 100 pzas. Weight x 100 pcs.		Pqt. Unit. Pzas. Pcs.	Unit Ctn. Pzas. Pcs.	Ship Ctn. Pzas. Pcs.	Std. Pkg. Pzas. Pcs.
			mm	inch.					kg	Lb				
 NIPLE	NI-13	04.21.2576	12.7	1/2	28.6	1 1/8	19.8	.78	3	6.6	25		900	
	NI-19	04.21.2577	19.0	3/4	35	1 3/8	20.1	.79	5	11.0	25		650	
	NI-25	04.21.2573	25.4	1	38	1 1/2	24.9	.98	10	22.0	25		225	
	NI-32	04.21.3233	31.7	1 1/4	41	1 5/8	25.4	1	10	22.0	10		200	
	NI-38	04.21.3234	38.1	1 1/2	44	1 3/4	25.9	1.02	12	26.5	10		150	
	NI-50	04.21.3235	50.8	2	51	2	26.7	1.05	20	44.0	10		60	
RAWELT, S.A. de C.V.										 Una División del Grupo REVUELTA				
4 - IV - 2024														