

Datos para selección y pedidos

Tablero FC y SBM para interruptor principal, 440/254 V, 3 fases, 4 hilos (Tabla 20)

Tipo de tablero	Capacidad en barras "A"	Alto		Frente		Fondo		Espacio util		Numero de parte
		pulg	mm	pulg	mm	pulg	mm	pulg	mm	
FCI	1200	90	2,286.00	38	965.20	28	711.20	35	889.00	MEX:FC190MB1200
FCII	1600	90	2,286.00	38	965.20	38	965.20	35	889.00	MEX:FC290MB1600
FCIII	2000	90	2,286.00	38	965.20	48	1,219.20	30	762.00	MEX:FC390MB2000
FCIII	3000	90	2,286.00	38	965.20	48	1,219.20	30	762.00	MEX:FC390MB3000
SBMI	1250	90	2,286.00	38	965.20	28	711.20	47.5	1,206.50	MEX:SBM190MB1250
SBMII	1600	90	2,286.00	38	965.20	38	965.20	47.5	1,206.50	MEX:SBM290MB1600
SBMII	2000	90	2,286.00	38	965.20	38	965.20	47.5	1,206.50	MEX:SBM390MB2000
SBMIII	3200	90	2,286.00	38	965.20	48	1,219.20	47.5	1,206.50	MEX:SBM390MB3200

Tablero FC y SBM para zapatas principales, 440/254 V, 3 fases, 4 hilos (Tabla 21)

Tipo de tablero	Capacidad en barras "A"	Alto		Frente		Fondo		Espacio util		Numero de parte
		pulg	mm	pulg	mm	pulg	mm	pulg	mm	
FCI	1200	90	2,286.00	38	965.20	28	711.20	65	1,651.00	MEX:FC190ML1200
FCII	1600	90	2,286.00	38	965.20	38	965.20	65	1,651.00	MEX:FC290ML1600
FCIII	2000	90	2,286.00	38	965.20	48	1,219.20	65	1,651.00	MEX:FC390ML2000
FCIII	3000	90	2,286.00	38	965.20	48	1,219.20	65	1,651.00	MEX:FC390ML3000
SBMI	1250	90	2,286.00	38	965.20	28	711.20	65	1,651.00	MEX:SBM190ML1250
SBMII	1600	90	2,286.00	38	965.20	38	965.20	65	1,651.00	MEX:SBM290ML1600
SBMII	2000	90	2,286.00	38	965.20	38	965.20	65	1,651.00	MEX:SBM390ML2000
SBMIII	3200	90	2,286.00	38	965.20	48	1,219.20	65	1,651.00	MEX:SBM390ML3200

Selección del interruptores principal, Interruptor termomagnético (Tabla 21)

Tipo de interruptor	Corriente máxima	Capacidad interruptiva (kA)				Numero de parte
		240 V	480 V	600 V	250 Vcd	
JXD	300	65	35	25	30	MX:JXD63B300
	350					MX:JXD63B350
	400					MX:JXD63B400
LXD	500	65	35	25	30	MX:LXD63B500
	600					MX:LXD63B600
LMXD	700	65	50	25	30	MX:LMXD63B700
	800					MX:LMXD63B800
ND	1000	65	50	25	30	MX:NXD63B100
	1200					MX:NXD63B120

Selección del interruptores principal, Interruptor electromagnetico unidad disparo ETU45B, LSIN (Tabla 22)

Tipo de interruptor	Corriente máxima	Ejecución	Capacidad interruptiva (kA)	Numero de parte
			500 V	
3WL1108-2EB34-1AA2	800	Fijo	55	3WL11082EB341AA2
3WL1112-2EB34-1AA2	1250	Fijo	55	3WL11122EB341AA2
3WL1116-2EB34-1AA2	1600	Fijo	55	3WL11162EB341AA2
3WL1220-2EB34-1AA2	2000	Fijo	66	3WL12202EB341AA2
3WL1225-2EB34-1AA2	2500	Fijo	66	3WL12252EB341AA2
3WL1232-3EB34-1AA2	3200	Fijo	80	3WL12323EB341AA2
3WL1108-2EB37-1AA2	800	Removable	55	3WL11082EB371AA2
3WL1112-2EB37-1AA2	1250	Removable	55	3WL11122EB371AA2
3WL1116-2EB37-1AA2	1600	Removable	55	3WL11162EB371AA2
3WL1220-2EB37-1AA2	2000	Removable	66	3WL11202EB371AA2
3WL1225-2EB37-1AA2	2500	Removable	66	3WL11252EB371AA2
3WL1232-3EB37-1AA2	3200	Removable	80	3WL11323EB371AA2