

Capacidad interruptiva

Tipo de interruptor	RMS Amperes Simétricos (KA)										
	UL 489 AIR (File E10848)					IEC 947-2					
	V CA (50/60 Hz)			V CD		V CA (50/60 Hz)					
	240	480	600	250	500	220/240		380/415		500	
						Icu	Ics	Icu	Ics	Icu	Ics
FXD6	65	35	22	30 (2-P)	18 (3-P)	65	33	35	9	—	—
HFXD6	100	65	25	30 (2-P)	25 (3-P)	100	50	65	33	—	—

Ajuste de rango de disparo instantáneo

Amperaje del interruptor	Valores Nominales Instantáneos							
	±20% Baja Tol.	2	3	4	5	6	7	±20% Alta Tol.
125-150	800	900	1000	1100	1200	1300	1400	1500
175-200	900	1060	1210	1370	1520	1780	1930	2000
225-250	1100	1300	1500	1700	1900	2100	2300	2500

Zapatas por 75 °C por Hilo

Material	Calibre de cable	Número de catálogo
Al	(1) #6—350 kcmil Cu (1) #4—350 kcmil Al	MX:TA1FD350A

Accesorios internos



Control de voltaje		Número de catálogo
CA	CD	
Bobina de disparo		
120		MX:S01FD60
Bobina de mínima tensión		
240		MX:U03FD60
480		MX:U06FD60
Contactos Auxiliares		
480		MX:A01FD64