# Product data sheet

Specifications



# Safety switch, heavy duty, non fusible, 60A, 3 wire, 3 pole, 60HP, 600V AC/DC, NEMA 3R, bolt on hub provision

HU362RB

① Discontinued

() Discontinued on: Jun 23, 2023

# Product availability: Stock - Normally stocked in distribution facility

### Main

Single Throw Safety Switch
Heavy duty
Heavy application
Non-fusible disconnect
None
3 phase
3
60 A
600 V AC/DC
NEMA 3R galvannealed steel
10 hp at 240 V AC 50-60 Hz for 1 phase motors 20 hp at 240 V AC 50-60 Hz for 3 phase motors 25 hp at 480 V AC 50-60 Hz for 1 phase motors 50 hp at 480 V AC 50-60 Hz for 3 phase motors 30 hp at 600 V AC 50-60 Hz for 1 phase motors 60 hp at 600 V AC 50-60 Hz for 3 phase motors 10 hp at 250 V DC 30 hp at 600 V DC

## Complementary

Mounting Type	Surface
Electrical Connection	Lugs
Wiring Configuration	3-wire
Wire Size	AWG 14AWG 3 copper AWG 12AWG 3 aluminium
Tightening Torque	50 lbf.in (5.65 N.m) (AWG 3) 45 lbf.in (5.08 N.m) (AWG 6AWG 4) 40 lbf.in (4.52 N.m) 0.01 in² (8.367 mm²) (AWG 8) 50 lbf.in (5.65 N.m) 0.000.01 in² (2.065.261 mm²) (AWG 14AWG 10)
Depth	6.38 in (162.05 mm)
Width	10.5 in (266.70 mm)
Height	21.25 in (539.75 mm)
Net Weight	15.43 lb(US) (7 kg)

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

## Environment

Certifications U

UL listed file E2875

# Ordering and shipping details

Category	US10DE100009
Discount Schedule	0DE1
Gtin	785901505617
Returnability	Yes
Country Of Origin	US

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	7.20 in (18.3 cm)
Package 1 Width	11.22 in (28.5 cm)
Package 1 Length	19.92 in (50.6 cm)
Package 1 Weight	15.20 lb(US) (6.895 kg)
Unit Type Of Package 2	PAL
Number Of Units In Package 2	40
Package 2 Height	45.50 in (115.57 cm)
Package 2 Width	40.00 in (101.6 cm)
Package 2 Length	48.00 in (121.92 cm)
Package 2 Weight	646.00 lb(US) (293.02 kg)

## **Contractual warranty**

Warranty

18 months

## Sustainability Screen

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Mercury Free
Rohs Exemption Information Yes
Pvc Free

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

## Product data sheet

#### **Dimensions Drawings**

#### Approximate Dimensions

