



Load center, QO, 1 phase, 12 spaces, 12 circuits, 100A convertible main breaker, NEMA3R, UL

QO112M100RB



! Discontinued on: Sep 1, 2020

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

| Marketing Trade Name | QO | |
|----------------------|------------------------|--|
| Product Type | Load Center | |
| Enclosure Type | Weatherproof enclosure | |
| Cover Type | Surface cover | |

Complementary

| Pon Convertible Mains (Lugs) | Main breaker |
|--|------------------------------------|
| Rated Current | 100 A |
| Number Of Spaces | 12 |
| Max Short Circuit Current Rating | 22 kA |
| Maximum Number Of Single Pole Circuits | 12 |
| Maximum Number Of Tandem Breakers | 0 |
| Number Of Phases | 1 phase |
| Voltage Rating | 120/240 V AC |
| Wire Size | AWG 6AWG 1 aluminium/copper |
| Ground Bar | Grounding bar (ordered separately) |
| Electrical Connection | Lugs |
| Wiring Configuration | 3-wire |
| Busbar Material | Tin plated copper: busbar |
| Enclosure Material | Welded galvannealed steel |
| Surface Finish | Baked enamel Gray |
| Box Number | 3R |
| Height | 18.94 in (481 mm) |
| Width | 14.76 in (375 mm) |

Environment

| Enclosure Rating | NEMA 3R outdoor |
|-----------------------------|-----------------|
| Ambient Air Temperature For | 23 °F (-5 °C) |
| Operation | 104 °F (40 °C) |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Product Certifications UL Listed

Ordering and shipping details

| Category | US1DE3A00002 |
|-------------------|--------------|
| Discount Schedule | DE3A |
| Gtin | 785901867876 |
| Returnability | No |
| Country Of Origin | US |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|-------------------------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 20.70 in (52.578 cm) |
| Package 1 Width | 4.80 in (12.192 cm) |
| Package 1 Length | 15.50 in (39.37 cm) |
| Package 1 Weight | 21.88 lb(US) (9.925 kg) |

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

| | Reach Free Of Svhc | |
|-----------------------|----------------------------|---|
| ② | Toxic Heavy Metal Free | |
| | Mercury Free | |
| ② | Rohs Exemption Information | Yes |
| | | |
| Eu Rohs Directive | | Compliant |
| | | EU RoHS Declaration |
| China Rohs Regulation | | China RoHS declaration |
| | | Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Cali | fornia Proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |