Product data sheet

Specifications







Mini circuit breaker, QO, 40A, 3 pole, 120/240VAC, 10kA, plug in

QO340

Product availability: Stock - Normally stocked in distribution facility

Price*: 248.00 USD

Main

Product Miniature circuit-breaker Range QO Current Rating 40 A Voltage Rating 120/240 V AC 240 V AC 120 V AC Mounting Type Plug-in Number Of Poles 3P Circuit Breaker Type Standard Ratings HACR rated		
Current Rating 40 A Voltage Rating 120/240 V AC 240 V AC 120 V AC Mounting Type Plug-in Number Of Poles 3P Circuit Breaker Type Standard Ratings HACR rated	Product	Miniature circuit-breaker
Voltage Rating 120/240 V AC 240 V AC 120 V AC 120 V AC 120 V AC Mounting Type Plug-in Number Of Poles 3P Circuit Breaker Type Standard Ratings HACR rated	Range	QO
240 V AC 120 V AC Mounting Type Plug-in Number Of Poles 3P Circuit Breaker Type Standard Ratings HACR rated	Current Rating	40 A
120 V AC Mounting Type Plug-in Number Of Poles 3P Circuit Breaker Type Standard Ratings HACR rated	Voltage Rating	120/240 V AC
Mounting Type Plug-in Number Of Poles 3P Circuit Breaker Type Standard Ratings HACR rated		240 V AC
Number Of Poles 3P Circuit Breaker Type Standard Ratings HACR rated		120 V AC
Circuit Breaker Type Standard Ratings HACR rated	Mounting Type	Plug-in
Ratings HACR rated	Number Of Poles	3P
	Circuit Breaker Type	Standard
Flectrical Connection Box lugs	Ratings	HACR rated
	Electrical Connection	Box lugs

Complementary

Interrupt Rating	10 kA 120/240 V AC
	10 kA 240 V AC
	10 kA 120 V AC
Number Of Panel Spaces	3
Wire Size	AWG 8AWG 2 copper or aluminium
Tightening Torque	44.25 lbf.in (5 N.m)
Height	2.99 in (76 mm)
Width	2.24 in (57 mm)
Depth	2.91 in (74 mm)
Net Weight	0.80 lb(US) (0.363 kg)

Environment

Certifications	UL Listed CSA
Ambient Rating	104 °F (40 °C)

Ordering and shipping details

Category	US1DE2A00012
Discount Schedule	DE2A
Gtin	785901400769
Returnability	Yes

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Country	Of	Origin	
---------	----	--------	--

Packing Units

r adning Offics	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.30 in (5.84 cm)
Package 1 Width	3.20 in (8.13 cm)
Package 1 Length	3.40 in (8.64 cm)
Package 1 Weight	12.80 oz (362.88 g)
Unit Type Of Package 2	BB1
Number Of Units In Package 2	3
Package 2 Height	3.30 in (8.382 cm)
Package 2 Width	2.80 in (7.112 cm)
Package 2 Length	6.80 in (17.272 cm)
Package 2 Weight	2.55 lb(US) (1.157 kg)
Unit Type Of Package 3	CAR
Number Of Units In Package 3	3
Package 3 Height	3.30 in (8.382 cm)
Package 3 Width	3.50 in (8.89 cm)
Package 3 Length	6.80 in (17.272 cm)
Package 3 Weight	2.55 lb(US) (1.157 kg)

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



RoHS/REACh

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Halogen Free Product

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Circularity Profile	No need of specific recycling operations