





Load center, QO, 3 phase, 3 spaces, 3 circuits, 60A main lugs, NEMA3R, neutral gnd bar, UL

QO403L60NRB

Product availability: Stock - Normally stocked in distribution

Price*: 177.00 USD

Main

Marketing Trade Name	QO
Product Type	Load Center
Enclosure Type	Weatherproof enclosure
Cover Type	Surface cover

Complementary

J	
Tightening Torque	Main lugs 35 lb.in, AWG 14AWG 10, aluminium/copper Main lugs 50 lb.in, AWG 3AWG 1, aluminium/copper Main lugs 40 lb.in, AWG 8AWG 4, aluminium/copper Main lugs 35 lb.in, AWG 12AWG10, aluminium/copper
Pon Convertible Mains (Lugs)	Fixed Mains (lugs)
Rated Current	60 A
Number Of Spaces	3
Max Short Circuit Current Rating	65 kA
Maximum Number Of Single Pole Circuits	3
Maximum Number Of Tandem Breakers	0
Number Of Phases	3 phase
Voltage Rating	208Y/120 V AC 240/120 V delta AC 240 V delta AC
Wire Size	AWG 10AWG 6 copper
Ground Bar	Grounding bar (ordered separately)
Electrical Connection	Lugs
Wiring Configuration	3-wire 4-wire
Busbar Material	Tin plated aluminium: busbar
Enclosure Material	Welded galvannealed steel
Surface Finish	Baked enamel Gray
Box Number	10R
Height	13.19 in (335 mm)
Width	6.93 in (176 mm)
Depth	4.13 in (105 mm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Net Weight 9.26 lb(US) (4.200 kg)

Environment

Enclosure Rating	NEMA 3R outdoor	
Ambient Air Temperature For Operation	23 °F (-5 °C) 104 °F (40 °C)	
Product Certifications	UL Listed	

Ordering and shipping details

Category	US10DE300017	
Discount Schedule	0DE3	
Gtin	785901051718	
Returnability	Yes	
Country Of Origin	MX	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5.12 in (13.0 cm)
Package 1 Width	8.39 in (21.3 cm)
Package 1 Length	15.00 in (38.1 cm)
Package 1 Weight	8.11 lb(US) (3.68 kg)
Unit Type Of Package 2	PAL
Number Of Units In Package 2	105
Package 2 Height	40.00 in (101.6 cm)
Package 2 Width	40.00 in (101.6 cm)
Package 2 Length	48.00 in (121.92 cm)
Package 2 Weight	860.77 lb(US) (390.44 kg)

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

②	Reach Free Of Svhc	
9	Toxic Heavy Metal Free	
②	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov