



RW Thermal Overload Relays 0.28...140 A

- Bimetallic overload relay with trip class 10
- Phase failure sensitivity
- Temperature compensation
- Manual or automatic reset
- Direct mounting to mini-contactors and contactors
- Allow individual mounting by means of an accessory¹⁾
- Adjustable multifunction button with the functions: HAND, AUTO, H or A
- Auxiliary contacts 1NO + 1NC



Direct mounting Screw terminal	Current range (A)	Diagram	Maximum fuse (gL/gG) ²⁾	Blue version		Weight kg
				Code	Part Number	
CW07 CWC07...16	0.28...0.4		2	RW17-1D3-D004	12450892	0.155
	0.4...0.63		2	RW17-1D3-C063	12450895	
	0.56...0.8		2	RW17-1D3-D008	12450896	
	0.8...1.2		4	RW17-1D3-D012	12450897	
	1.2...1.8		6	RW17-1D3-D018	12450898	
	1.8...2.8		6	RW17-1D3-D028	12450899	
	2.8...4		10	RW17-1D3-U004	12450900	
	4...6.3		16	RW17-1D3-D063	12450901	
	5.6...8		20	RW17-1D3-U008	12450903	
	7...10		25	RW17-1D3-U010	12450905	
	8...12.5		25	RW17-1D3-D125	12450906	
	10...15		35	RW17-1D3-U015	12450907	
	11...17		40	RW17-1D3-U017	12450908	
	CWC025		7...10	25	RW17-2D3-U010	
8...12.5		25	RW17-2D3-D125	12450910		
10...15		35	RW17-2D3-U015	12450911		
11...17		40	RW17-2D3-U017	12450912		
15...23		50	RW17-2D3-U023	12450913		
22...32		63	RW17-2D3-U032	12450914		
CWB9...38		0.28...0.4		2	RW27-2D3-D004	12140441
	0.43...0.63	2		RW27-2D3-C063	12140442	
	0.56...0.8	2		RW27-2D3-D008	12140443	
	0.8...1.2	4		RW27-2D3-D012	12140444	
	1.2...1.8	6		RW27-2D3-D018	12140445	
	1.8...2.8	6		RW27-2D3-D028	12140446	
	2.8...4	10		RW27-2D3-U004	12140447	
	4...6.3	16		RW27-2D3-D063	12140448	
	5.6...8	20		RW27-2D3-U008	12140449	
	7...10	25		RW27-2D3-U010	12140450	
	8...12.5	25		RW27-2D3-D125	12140451	
	10...15	35		RW27-2D3-U015	12140452	
	11...17	40		RW27-2D3-U017	12140453	
	15...23	50		RW27-2D3-U023	12140454	
	22...32	63		RW27-2D3-U032	12140455	
	32...40	90		RW27-2D3-U040	12140456	
	CWB40...80	25...40		80	RW67-5D3-U040	13368960
32...50		80	RW67-5D3-U050	13368961		
40...57		100	RW67-5D3-U057	13368962		
50...63		100	RW67-5D3-U063	13368963		
57...70		125	RW67-5D3-U070	13368964		
63...80		125	RW67-5D3-U080	13368965		
CWB95...125		63...80	200	RW117-3D3-U080	14204758	0.480
	75...97	225	RW117-3D3-U097	14204759		
	90...112	250	RW117-3D3-U112	14204761		
	110...140	315	RW117-3D3-U140	14204762		

Notes: 1) Except for RW17-1D and RW17-2D.

2) Maximum fuse for Type 2 coordination (gL/gG).