



RSDX-300W-BB



RSDX-50W-BB



Uso exterior



Terminado en negro



Pantalla de Cristal



Ángulo 120°



Base soporte de fijación



-10 a 45 °C

NOM



CLAVE	TEMPERATURA	VOLTAJE	WATTS	LUMINOSIDAD	F.P.	MATERIAL	DIMENSIONES	IP
RSDX-10W-BB	6500K	110-265 V~	10W	1,200 Lm	≥.65	Al + Cr	94*73*19 mm	65
RSDX-10W-BC	3000K	110-265 V~	10W	1,140 Lm	≥.65	Al + Cr	94*73*19 mm	65
RSDX-20W-BB	6500K	110-265 V~	20W	2,400 Lm	≥.65	Al + Cr	110*87*23 mm	65
RSDX-20W-BC	3000K	110-265 V~	20W	2,280 Lm	≥.65	Al + Cr	110*87*23 mm	65
RSDX-30W-BB	6500K	110-265 V~	30W	3,600 Lm	≥.65	Al + Cr	147*113*28 mm	65
RSDX-30W-BC	3000K	110-265 V~	30W	3,420 Lm	≥.65	Al + Cr	147*113*28 mm	65
RSDX-50W-BB	6500K	110-265 V~	50W	6,000 Lm	≥.65	Al + Cr	189*146*33 mm	65
RSDX-50W-BC	3000K	110-265 V~	50W	5,700 Lm	≥.65	Al + Cr	189*146*33 mm	65
RSDX-100W-BB	6500K	110-265 V~	100W	12,000 Lm	≥.70	Al + Cr	246*189*35 mm	65
RSDX-100W-BC	3000K	110-265 V~	100W	11,400 Lm	≥.70	Al + Cr	246*189*35 mm	65
RSDX-150W-BB	6500K	110-265 V~	150W	18,000 Lm	≥.90	Al + Cr	277*215*37 mm	65
RSDX-200W-BB	6500K	110-265 V~	200W	24,000 Lm	≥.90	Al + Cr	348*255*38 mm	65
RSDX-300W-BB	6500K	110-265 V~	300W	36,000 Lm	≥.90	Al + Cr	408*309*45 mm	65