

REFLECTOR RST

TECNOLED^{PLUS}
Ilumina ahorrando



RST-200W



RST-50W-BB



Uso exterior



Terminado en negro



Pantalla de Cristal



Ángulo 120°



Base soporte de fijación



-10 a 45 °C

NOM



CLAVE	TEMPERATURA	VOLTAJE	WATTS	LUMINOSIDAD	F.P.	MATERIAL	DIMENSIONES	IP
RST-20W-BB	6500K	100-277 V~	20W	2,100 Lm	≥.95	Al + Cr	100*94*26 mm	65
RST-20W-BC	3500K	100-277 V~	20W	2,000 Lm	≥.95	Al + Cr	100*94*26 mm	65
RST-30W-BB	6500K	100-277 V~	30W	3,500 Lm	≥.95	Al + Cr	124*120*27 mm	65
RST-30W-BC	3500K	100-277 V~	30W	3,320 Lm	≥.95	Al + Cr	124*120*27 mm	65
RST-50W-BB	6500K	100-277 V~	50W	5,300 Lm	≥.95	Al + Cr	179*149*28 mm	65
RST-50W-BC	3500K	100-277 V~	50W	5,040 Lm	≥.95	Al + Cr	179*149*28 mm	65
RST-100W	6500K	100-277 V~	100W	10,300 Lm	≥.95	Al + Cr	232*208*36 mm	65
RST-100W-BC	3500K	100-277 V~	100W	9,790 Lm	≥.95	Al + Cr	232*208*36 mm	65
RST-200W	6500K	100-277 V~	200W	20,000 Lm	≥.95	Al + Cr	368*297*44 mm	65

